

Dropout Europe Limited

+44 1572 338041

sales@drop-out.co.uk

www.drop-out.co.uk

Version 1.1

dropout®

DOAD128 Auto-drain



The **DOAD128** is designed to remove all contaminants from the Dropout units automatically. It has two 1/2" inlet connections enabling flexible installation. It is supplied with a metal blanking plug to block unused port.

Metal blanking plug (included)



- ✓ Drains all contaminants (liquid water & oil and solid particles)
- ✓ Automatic and manual drain options
- ✓ Maintenance free
- ✓ No mains power
- ✓ Easy to install

Save money, Save energy, Save time

“We at Dropout® are dedicated to solving your compressed air problems”

Technical Data

Features:

- ✓ Drains all contaminants (liquid water & oil and solid particles)
- ✓ Automatic and manual drain options
- ✓ Maintenance free
- ✓ No mains power
- ✓ Easy to install

Specification	P/N: DOAD128	
Inlet connections	(BSPT)	1/2"
Outlet connection	(BSPT)	1/8"
Dimensions	(mm)	187 x 70 Ø
Weight	(kg)	0.4
Material	Aluminium	
Operating pressure (min - max)	(bar g)	1 - 16
	(psi g)	15 - 232
Operating temperature (min - max)	(°C)	>0 to 80
	(°F)	>32 to 176

