



PCL Couplings & Adaptors



KF Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: Nito Kohki, Rectus 13, CEJN 315 - Nominal Bore: 7.6mm - Flow Rate @ 6bar: 2100 Ltr/min @ 0.5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -40°C to +100°C.

| Part No. | Old Ref. | Description (mm) | Price £ |
|----------|----------|--------------------|---------|
| AC78CM | JCM04 | 1/4" BSPT Male | 10.72 |
| AC78EM | JCM06 | 3/8" BSPT Male | 10.72 |
| AC78JM | JCM08 | 1/2" BSPT Male | 10.72 |
| AC78CF | JCF04 | 1/4" BSPP Female | 10.72 |
| AC78EF | JCF06 | 3/8" BSPP Female | 10.72 |
| AC78JF | JCF08 | 1/2" BSPP Female | 10.72 |
| AC7806 | JCH04 | 1/4" (6) Hosetail | 10.72 |
| AC7808 | JCH05 | 5/16" (8) Hosetail | 10.72 |
| AC7810 | JCH06 | 3/8" (10) Hosetail | 10.72 |
| AC7813 | JCH08 | 1/2" (12) Hosetail | 10.72 |

Euro Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: ARO210, Rectus14, PCL Euro range - Nominal Bore: 5.5mm - Flow Rate @ 6bar: 650 Ltr/min @ 0.5bar p.d - Max - Working Pressure: 200psi (14bar) - Temperature Range: -40°C to +100°C.

| Part No. | Old Ref. | Description (mm) | Price £ |
|----------|----------|--------------------|---------|
| AC61CM | PCMA04 | 1/4" BSPT Male | 6.38 |
| AC61EM | PCMA06 | 3/8" BSPT Male | 6.38 |
| AC61JM | PCMA08 | 1/2" BSPT Male | 6.38 |
| AC61CF | PCFA04 | 1/4" BSPP Female | 6.38 |
| AC61EF | PCFA06 | 3/8" BSPP Female | 6.38 |
| AC61JF | PCFA08 | 1/2" BSPP Female | 6.38 |
| AC61R | PCHA04 | 1/4" (6) Hosetail | 6.38 |
| AC61S | PCHA05 | 5/16" (8) Hosetail | 6.38 |
| AC61T | PCHA06 | 3/8" (10) Hosetail | 6.38 |

PF Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: Schrader Standard Duty, Rectus 17, Single Action & Positive Lock - Nominal Bore: 5.0mm - Flow Rate @ 6bar: 2200Ltr/min @ 5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -40°C to +100°C.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AC77CM | 1/4" BSPT Male | 8.24 |
| AC77EM | 3/8" BSPT Male | 8.24 |
| AC77JM | 1/2" BSPT Male | 8.24 |
| AC77CF | 1/4" BSPP Female | 8.24 |
| AC77EF | 3/8" BSPP Female | 8.24 |
| AC77JF | 1/2" BSPP Female | 8.24 |
| AC7706 | 1/4" (6) Hosetail | 8.24 |
| AC7708 | 5/16" (8) Hosetail | 8.24 |
| AC7710 | 3/8" (10) Hosetail | 8.24 |
| AC7713 | 1/2" (12) Hosetail | 8.24 |

KF Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AA7802 | 1/4" BSPT Male | 1.86 |
| AA7803 | 3/8" BSPT Male | 2.13 |
| AA7804 | 1/2" BSPT Male | 3.99 |
| AA7806 | 1/4" BSPP Female | 2.20 |
| AA7807 | 3/8" BSPP Female | 2.85 |
| AA7808 | 1/2" BSPP Female | 3.99 |
| AA7810 | 1/4" (6) Hosetail | 1.86 |
| AA7811 | 5/16" (8) Hosetail | 1.86 |
| AA7812 | 3/8" (10) Hosetail | 1.86 |
| AA7813 | 1/2" (12) Hosetail | 2.65 |

Euro Adaptor



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: ARO210, Rectus 14.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| ACA6923 | 1/4" BSPT Male | 1.29 |
| ACA6924 | 1/4" BSPP Female | 1.29 |
| ACA6912 | 1/4" (6) Hosetail | 1.29 |
| ACA6922 | 5/16" (8) Hosetail | 1.29 |
| ACA6930 | 3/8" (10) Hosetail | 1.29 |

PF Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail.

| Part No. | Schrader | Description (mm) | Price £ |
|----------|----------|--------------------|---------|
| AA7702 | 8050B-11 | 1/4" BSPT Male | 1.86 |
| AA7703 | - | 3/8" BSPT Male | 2.13 |
| AA7706 | 8278L-11 | 1/4" BSPP Female | 1.86 |
| AA7707 | - | 3/8" BSPP Female | 2.13 |
| AA7710 | 8787-11 | 1/4" (6) Hosetail | 1.86 |
| AA7711 | 9750-11 | 5/16" (8) Hosetail | 1.86 |
| AA7712 | 8788-11 | 3/8" (10) Hosetail | 1.86 |



Now Available
Please Call Our Sales team For Pricing & Info

Airflow Couplings



PNEUMATIC QUICK RELEASE COUPLINGS - BSPT Male, BSPP Female & Hosetail - Used in fixed applications - Interchangeable: Rectus 19 & CEJN295 - Nominal Bore: 4.8mm - Max. Flow Rate: 43cfm@100psi - Max. Working Pressure: 200psi (14bar) - Temp. Range: -40°C to +100°C - Type: Single Action

| Part No. | Old Ref. | Description (mm) | Price £ |
|----------|----------|--------------------|---------|
| AC21CM | PCM04 | 1/4" BSPT Male | 7.15 |
| AC21EM | PCM06 | 3/8" BSPT Male | 8.48 |
| AC21JM | PCM08 | 1/2" BSPT Male | 8.48 |
| AC21CF | PCF04 | 1/4" BSPP Female | 7.15 |
| AC21EF | PCF06 | 3/8" BSPP Female | 8.48 |
| AC21JF | PCF08 | 1/2" BSPP Female | 8.48 |
| AC21R | PCH04 | 1/4" (6) Hosetail | 8.48 |
| AC21S | PCH05 | 5/16" (8) Hosetail | 8.48 |
| AC21T | PCH06 | 3/8" (10) Hosetail | 8.48 |

Safeflow Safety Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Two Stage Self Venting Conforms To: ISO 4414:1998 and EN 983:1996 - Creates A Safe Compressed Air Environment - Compatible With Genuine PCL Standard Adaptors - Safe And Simple To Use - Enhances Workshop Safety - Prevents Hose Whip - Interchangeable: Rectus 19, CEJN 295.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| SC21CM | 1/4" BSPT Male | 9.50 |
| SC21EM | 3/8" BSPT Male | 11.25 |
| SC21JM | 1/2" BSPT Male | 11.25 |
| SC21CF | 1/4" BSPP Female | 9.50 |
| SC21EF | 3/8" BSPP Female | 11.25 |
| SC21JF | 1/2" BSPP Female | 11.25 |
| SC21R | 1/4" (6) Hosetail | 11.25 |
| SC21S | 5/16" (8) Hosetail | 11.25 |
| SC21T | 3/8" (10) Hosetail | 11.25 |

Standard Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Suitable For Air Flow, Vertex and Safe Flow Couplings.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| ACA2593 | 1/4" BSPT Male | 1.25 |
| ACA6909 | 3/8" BSPT Male | 1.25 |
| ACA6584 | 1/2" BSPT Male | 2.95 |
| ACA2746 | 1/4" BSPP Female | 1.25 |
| ACA6582 | 3/8" BSPP Female | 2.95 |
| ACA6583 | 1/2" BSPP Female | 3.65 |
| ACA2486 | 3/16" (5) Hosetail | 1.25 |
| ACA1793 | 1/4" (6) Hosetail | 1.25 |
| ACA2487 | 5/16" (8) Hosetail | 1.25 |
| ACA2488 | 3/8" (10) Hosetail | 1.25 |
| ACA9438 | 1/2" (12) Hosetail | 2.95 |

Vertex Airflow Couplings



PNEUMATIC QUICK RELEASE COUPLINGS - BSPT Male, BSPP Female & Hosetail - Trailing Hose Application - Interchangeable: Rectus 19 & CEJN295 - Prevents Accidental Disconnection - Double action

| Part No. | Old Ref. | Description (mm) | Price £ |
|----------|----------|--------------------|---------|
| AC91CM | PCMV04 | 1/4" BSPT Male | 7.15 |
| AC91EM | PCMV06 | 3/8" BSPT Male | 8.48 |
| AC91JM | PCMV08 | 1/2" BSPT Male | 8.48 |
| AC91CF | PCFV04 | 1/4" BSPP Female | 7.15 |
| AC91EF | PCFV06 | 3/8" BSPP Female | 8.48 |
| AC91JF | PCFV08 | 1/2" BSPP Female | 8.48 |
| AC91R | PCHV04 | 1/4" (6) Hosetail | 8.48 |
| AC91S | PCHV05 | 5/16" (8) Hosetail | 8.48 |
| AC91T | PCHV06 | 3/8" (10) Hosetail | 8.48 |

Twin Airflow Couplings



Standard and Vertex.

| Part No. | Old Ref. | Description | Price £ |
|----------|----------|--------------------------------|---------|
| AC6103 | PCLY | Twin Airflow Standard Coupling | 26.52 |
| AC6503 | PCLVY | Twin Airflow Vertex Coupling | 26.52 |

Safety Adaptor



BSPT Male Anti Whip.

| Part No. | Old Ref. | Description | Price £ |
|----------|----------|----------------|---------|
| ACA9101 | PM04S | 1/4" BSPT Male | 4.90 |

Mini Couplings



PCL Air Technology: BSPP Male, BSPP Female, Interchangeable With: Rectus 21, Camozzi, Norgren 233 - Nominal Bore: 5.0mm - Flow Rate @ 6bar: 560Ltr/min @ 0.5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -40°C to +100°C

| Part No. | Description (mm) | Price £ |
|----------|------------------|---------|
| AC11AM | 1/8" BSPP Male | 5.26 |
| AC11CM | 1/4" BSPP Male | 5.26 |
| AC11AF | 1/8" BSPP Female | 5.26 |
| AC11CF | 1/4" BSPP Female | 5.26 |

For Tubes & Hoses

See Section 1 & 16



Mini Adaptors



PCL Air Technology: BSPP Male, BSPP Female.

| Part No. | Description | Price £ |
|----------|------------------|---------|
| AA11AM | 1/8" BSPP Male | 1.56 |
| AA11CM | 1/4" BSPP Male | 1.56 |
| AA11AF | 1/8" BSPP Female | 1.56 |
| AA11CF | 1/4" BSPP Female | 1.56 |
| AA1106 | 6mm Hosetail | 1.56 |
| AA1109 | 9mm Hosetail | 1.56 |

ISO-B12 Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AA7502 | 1/4" BSPT Male | 1.86 |
| AA7503 | 3/8" BSPT Male | 2.13 |
| AA7504 | 1/2" BSPT Male | 3.99 |
| AA7506 | 1/4" BSPP Female | 1.86 |
| AA7507 | 3/8" BSPP Female | 2.13 |
| AA7508 | 1/2" BSPP Female | 3.99 |
| AA7510 | 1/4" (6) Hosetail | 1.86 |
| AA7511 | 5/16" (8) Hosetail | 1.86 |
| AA7512 | 3/8" (10) Hosetail | 1.86 |
| AA7513 | 1/2" (12) Hosetail | 1.86 |

XF Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: CEJN 320, Rectus 25 & 26, Parker 35.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AA7101 | 1/8" BSPT Male | 1.86 |
| AA7102 | 1/4" BSPT Male | 1.86 |
| AA7103 | 3/8" BSPT Male | 2.13 |
| AA7104 | 1/2" BSPT Male | 3.99 |
| AA7105 | 1/8" BSPP Female | 1.86 |
| AA7106 | 1/4" BSPP Female | 1.86 |
| AA7107 | 3/8" BSPP Female | 2.13 |
| AA7108 | 1/2" BSPP Female | 3.99 |
| AA7110 | 1/4" (6) Hosetail | 1.86 |
| AA7111 | 5/16" (8) Hosetail | 1.86 |
| AA7112 | 3/8" (10) Hosetail | 1.86 |
| AA7113 | 1/2" (12) Hosetail | 1.86 |

ISO-B12 Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: ISO 6150-B12, CEJN 310, Rectus 23 & 24, Parker, Dynaquip DC3, Hanson 3000, US-MIL C4109 - Nominal Bore: 5.5mm - Flow Rate @ 6bar: 1100Ltr/min @ 5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -40°C to +100°C.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AC75CM | 1/4" BSPT Male | 10.72 |
| AC75EM | 3/8" BSPT Male | 10.72 |
| AC75JM | 1/2" BSPT Male | 10.72 |
| AC75CF | 1/4" BSPP Female | 10.72 |
| AC75EF | 3/8" BSPP Female | 10.72 |
| AC75JF | 1/2" BSPP Female | 10.72 |
| AC7506 | 1/4" (6) Hosetail | 10.72 |
| AC7508 | 5/16" (8) Hosetail | 10.72 |
| AC7510 | 3/8" (10) Hosetail | 10.72 |
| AC7513 | 1/2" (12) Hosetail | 10.72 |

XF High Flow Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: CEJN 320, Rectus 25 & 26, Parker 35 - Nominal Bore: 7.4mm - Flow Rate @ 6bar: 2200Ltr/min @ 0.5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -40°C to +100°C.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AC71CM | 1/4" BSPT Male | 8.24 |
| AC71EM | 3/8" BSPT Male | 8.24 |
| AC71JM | 1/2" BSPT Male | 8.24 |
| AC71CF | 1/4" BSPP Female | 8.24 |
| AC71EF | 3/8" BSPP Female | 8.24 |
| AC71JF | 1/2" BSPP Female | 8.24 |
| AC7106 | 1/4" (6) Hosetail | 8.24 |
| AC7108 | 5/16" (8) Hosetail | 8.24 |
| AC7110 | 3/8" (10) Hosetail | 8.24 |
| AC7113 | 1/2" (12) Hosetail | 8.24 |

XF Adaptors



Safety Adaptor - BSPT Male, Interchangeable With: CEJN 320, Rectus 25 & 26, Parker 35.

| Part No. | Description (mm) | Price £ |
|------------|------------------|---------|
| AA7103/STY | 3/8" BSPT Male | 5.12 |



**See Section 1 & 2
For More Couplers**

ZF High Flow Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Interchangeable With: CEJN 410, Rectus 27, Parker 55 - Nominal Bore: 10.5mm - Flow Rate @ 6bar: 3000Ltr/min @ 5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -40°C to +100°C

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AC81CM | 1/4" BSPT Male | 26.20 |
| AC81EM | 3/8" BSPT Male | 26.20 |
| AC81JM | 1/2" BSPT Male | 26.20 |
| AC81LM | 3/4" BSPT Male | 26.20 |
| AC81CF | 1/4" BSPP Female | 26.20 |
| AC81EF | 3/8" BSPP Female | 26.20 |
| AC81JF | 1/2" BSPP Female | 26.20 |
| AC81LF | 3/4" BSPP Female | 26.20 |
| AC8108 | 5/16" (8) Hosetail | 26.20 |
| AC8110 | 3/8" (10) Hosetail | 26.20 |
| AC8113 | 1/2" (12) Hosetail | 26.20 |
| AC8116 | 5/8" (16) Hosetail | 26.20 |
| AC8119 | 3/4" (19) Hosetail | 26.20 |

ZF Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, For use With ZF Couplings - Corrosive Resistant Finish - Case Hardened For Longer Life.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AA8101 | 1/4" BSPT Male | 6.46 |
| AA8102 | 3/8" BSPT Male | 6.46 |
| AA8103 | 1/2" BSPT Male | 6.46 |
| AA8104 | 3/4" BSPT Male | 8.03 |
| AA8105 | 1/4" BSPP Female | 6.46 |
| AA8106 | 3/8" BSPP Female | 6.46 |
| AA8107 | 1/2" BSPP Female | 6.46 |
| AA8108 | 3/4" BSPP Female | 9.55 |
| AA8109 | 1/4" (6) Hosetail | 6.46 |
| AA8110 | 5/16" (8) Hosetail | 6.46 |
| AA8111 | 3/8" (10) Hosetail | 6.46 |
| AA8112 | 1/2" (12) Hosetail | 6.46 |
| AA8113 | 5/8" (16) Hosetail | 6.46 |
| AA8114 | 3/4" (19) Hosetail | 6.46 |

60 Series Couplings



PCL Air Technology: BSPT Male, BSPP Female.

| Part No. | Description | Price £ |
|----------|------------------|---------|
| AC4EM | 3/8" BSPT Male | 16.33 |
| AC4JM | 1/2" BSPT Male | 16.33 |
| AC4CF | 1/4" BSPP Female | 16.33 |
| AC4EF | 3/8" BSPP Female | 16.33 |
| AC4JF | 1/2" BSPP Female | 16.33 |
| AC4CM | 1/4" BSPT Male | 16.33 |

60 Series Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| ACA2657 | 1/4" BSPT Male | 3.88 |
| ACA2661 | 3/8" BSPT Male | 3.88 |
| ACA2653 | 1/4" BSPP Female | 3.88 |
| ACA2660 | 3/8" BSPP Female | 3.88 |
| ACA2654 | 5/16" (8) Hosetail | 3.88 |
| ACA2658 | 3/8" (10) Hosetail | 3.88 |
| ACA2659 | 1/2" (12) Hosetail | 3.88 |

60 Series Adaptors



Safety Adaptor - BSPT Male.

| Part No. | Description (mm) | Price £ |
|----------|------------------|---------|
| ACA9201 | 3/8" BSPT Male | 6.73 |

100 Series Couplings



PCL Air Technology: BSPT Male, BSPP Female.

| Part No. | Description | Price £ |
|----------|------------------|---------|
| AC5EM | 3/8" BSPT Male | 20.54 |
| AC5JM | 1/2" BSPT Male | 20.54 |
| AC5EF | 3/8" BSPP Female | 20.54 |
| AC5JF | 1/2" BSPP Female | 20.54 |

100 Series Adaptors



PCL Air Technology: BSPT Male, BSPP Female & Hosetail.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| ACA2999 | 3/8" BSPT Male | 3.88 |
| ACA3035 | 1/2" BSPT Male | 3.88 |
| ACA2994 | 3/8" BSPP Female | 3.88 |
| ACA3037 | 3/8" (8) Hosetail | 3.88 |
| ACA3036 | 1/2" (10) Hosetail | 3.88 |

100 Series Adaptors



Safety Adaptor - BSPT Male.

| Part No. | Description (mm) | Price £ |
|----------|------------------|---------|
| ACA9301 | 1/2" BSPT Male | 6.73 |



Now Available
Please Call Our Sales team For Pricing & Info

Multi-Fit Couplings



PCL Air Technology: BSPT Male, BSPP Female & Hosetail, Coupler Accepts: ISO B12, Rectus 14, 23, 25 & 26, Euro, CEJN 310, 410, PCL XF, ARO 210 Adaptors, Offering Good Airflow Characteristics With The Added Flexibility Of Accepting 3 Key, Adaptor Profiles, Euro, ISO B12 and XF, Steel Construction With Corrosive Resistant Finish - Nominal Bore: 5.0mm - Flow Rate @ 6bar: 1800Ltr/min @ 0.5bar p.d - Max - Working Pressure: 508psi (35bar) - Temperature Range: -20°C to +100°C.

| Part No. | Description (mm) | Price £ |
|----------|--------------------|---------|
| AC73CM | 1/4" BSPT Male | 10.72 |
| AC73EM | 3/8" BSPT Male | 10.72 |
| AC73JM | 1/2" BSPT Male | 10.72 |
| AC73CF | 1/4" BSPP Female | 10.72 |
| AC73EF | 3/8" BSPP Female | 10.72 |
| AC73JF | 1/2" BSPP Female | 10.72 |
| AC7306 | 1/4" (6) Hosetail | 10.72 |
| AC7308 | 5/16" (8) Hosetail | 10.72 |
| AC7310 | 3/8" (10) Hosetail | 10.72 |
| AC7313 | 1/2" (12) Hosetail | 10.72 |

Instant Air Couplings - Steel



PCL Air Technology: BSPP Male, BSPP Female & Hosetail, Broomwade - Steel - Nominal Bore: 5.6mm - Flow Rate @ 6bar: 54cfm - Max. Working Pressure: 250psi (17bar) - Temperature Range: -20°C to +80°C.

| Part No. | Old Ref: | Broomwade Ref - No. | Description (mm) | Price £ |
|----------|----------|---------------------|--------------------|---------|
| AC51CM | PCMI04 | PT8825 | 1/4" BSPP Male | 7.84 |
| AC51EM | PCMI06 | PT8827 | 3/8" BSPP Male | 7.84 |
| AC51JM | PCMI08 | PT9095 | 1/2" BSPT Male | 7.84 |
| AC51CF | PCFI04 | PT8823 | 1/4" Female | 7.84 |
| AC51EF | PCFI06 | PT8800 | 3/8" Female | 7.84 |
| AC51JF | PCFI08 | PT9096 | 1/2" Female | 7.84 |
| AC51R | PCHI04 | PT8800/SU4 | 1/4" (6) Hosetail | 7.84 |
| AC51S | PCHI05 | PT8800/SU5 | 5/16" (8) Hosetail | 7.84 |
| AC51T | PCHI06 | PT8800/SU6 | 3/8" (10) Hosetail | 7.84 |

Instant Air Fixed Adaptors - Steel



PCL Air Technology: BSPP Male, BSPP Female & Hosetail.

| Part No. | Old Ref: | Broomwade Ref - No. | Description (mm) | Price £ |
|----------|----------|---------------------|--------------------|---------|
| AA5102 | PMI04 | PT8808 | 1/4" BSPP Male | 4.38 |
| AA5103 | PMI06 | PT8817 | 3/8" BSPP Male | 4.38 |
| AA5106 | PFI04 | PT8806 | 1/4" BSPP Female | 4.38 |
| AA5107 | PFI06 | PT8802 | 3/8" BSPP Female | 4.38 |
| AA5110 | PHI04 | PT8802/SU4 | 1/4" (6) Hosetail | 4.38 |
| AA5111 | PHI05 | PT8802/SU5 | 5/16" (8) Hosetail | 4.38 |
| AA5112 | PHI06 | PT8802/SU6 | 3/8" (10) Hosetail | 4.38 |

Instant Air Swivel Adaptors - Steel



PCL Air Technology: BSPP Male, BSPP Female & Hosetail.

| Part No. | Old Ref: | Broomwade Ref - No. | Description (mm) | Price £ |
|----------|----------|---------------------|--------------------|---------|
| AA5302 | PMIS04 | PT8836 | 1/4" BSPP Male | 6.60 |
| AA5303 | PMIS06 | PT8838 | 3/8" BSPP Male | 6.60 |
| AA5306 | PFIS04 | PT8834 | 1/4" BSPP Female | 6.60 |
| AA5307 | PFIS06 | PT8804 | 3/8" BSPP Female | 6.60 |
| AA5310 | PHIS04 | PT8804/SU4 | 1/4" (6) Hosetail | 6.60 |
| AA5311 | PHIS05 | PT8804/SU5 | 5/16" (8) Hosetail | 6.60 |
| AA5312 | PHIS06 | PT8804/SU6 | 3/8" (10) Hosetail | 6.60 |

Instant Air Couplings - Brass



PCL Air Technology: BSPP Male, BSPP Female & Hosetail, Broomwade - Brass - Nominal Bore: 5.6mm - Flow Rate @ 6bar: 54cfm @ 100 psi - Max - Working Pressure: 250psi (17bar) - Temperature Range: -20°C to +80°C.

| Part No. | Old Ref: | Broomwade Ref - No. | Description (mm) | Price £ |
|----------|----------|---------------------|--------------------|---------|
| AC52CM | PCMI04B | PT8826 | 1/4" BSPP Male | 18.37 |
| AC52EM | PCMI06B | PT8828 | 3/8" BSPP Male | 18.37 |
| AC52CF | PCFI04B | PT8824 | 1/4" BSPP Female | 18.37 |
| AC52EF | PCFI06B | PT8801 | 3/8" BSPP Female | 18.37 |
| AC52R | PCHI04B | PT8801/SU4 | 1/4" (6) Hosetail | 18.37 |
| AC52S | PCHI05B | PT8801/SU5 | 5/16" (8) Hosetail | 18.37 |
| AC52T | PCHI06B | PT8801/SU6 | 3/8" (10) Hosetail | 18.37 |

Instant Air Fixed Adaptors - Brass



PCL Air Technology: BSPP Male, BSPP Female & Hosetail.

| Part No. | Old Ref. | Broomwade No. | Description (mm) | Price £ |
|----------|----------|---------------|--------------------|------------|
| AA5202 | PMI04B | PT8809 | 1/4" BSPP Male | 11.12 |
| AA5203 | PMI06B | PT8818 | 3/8" BSPP Male | 11.12 |
| AA5206 | PFI04B | PT8807 | 1/4" BSPP Female | 11.12 |
| AA5207 | PFI06B | PT8803 | 3/8" BSPP Female | 11.12 |
| AA5210 | PHI04B | PT8803/SU4 | 1/4" (6) Hosetail | 11.12 |
| AA5211 | PHI05B | PT8803/SU5 | 5/16" (8) Hosetail | 11.12 |
| AA5212 | PHI06B | PT8803/SU6 | 3/8" (10) Hosetail | 11.12 |

Instant Air Couplings - 1/2" Heavy Duty



PCL Air Technology: BSPP Male, BSPP Female & Hosetail - Nominal Bore: 8mm - Flow Rate @ 6bar: 70cfm - Max. Working Pressure: 250psi (17bar) - Temperature Range: -20°C to +80°C.

| Part No. | Old Ref. | Broomwade Ref. No. | Description (mm) | Price £ |
|----------|----------|--------------------|--------------------|------------|
| AC59JM | PCMI08H | PT8811 | 1/2" BSPP Male | 32.50 |
| AC59JF | PCFI08H | PT8812 | 1/2" BSPP Female | 32.50 |
| AC59V | PCHI08H | PT8813 | 1/2" (12) Hosetail | 32.50 |

Instant Air Swivel Adaptors - Brass



PCL Air Technology: BSPP Male, BSPP Female & Hosetail.

| Part No. | Old Ref. | Broomwade Ref. No. | Description (mm) | Price £ |
|----------|----------|--------------------|--------------------|------------|
| AA5402 | PMIS04B | PT8837 | 1/4" BSPP Male | 16.06 |
| AA5403 | PMIS06B | PT8839 | 3/8" BSPP Male | 16.06 |
| AA5406 | PFIS04B | PT8835 | 1/4" BSPP Female | 16.06 |
| AA5407 | PFIS06B | PT8805 | 3/8" BSPP Female | 16.06 |
| AA5410 | PHIS04B | PT8805/SU4 | 1/4" (6) Hosetail | 16.06 |
| AA5411 | PHIS05B | PT8805/SU5 | 5/16" (8) Hosetail | 16.06 |
| AA5412 | PHIS06B | PT8805/SU6 | 3/8" (10) Hosetail | 16.06 |

Instant Air Adaptors - 1/2" Heavy Duty



PCL Air Technology: BSPP Male, BSPP Female & Hosetail.

| Part No. | Old Ref. | Broomwade Ref. No. | Description (mm) | Price £ |
|----------|----------|--------------------|--------------------|------------|
| AA5904 | PMIS08H | PT8820 | 1/2" BSPP Male | 27.53 |
| AA5908 | PFIS08H | PT8821 | 1/2" BSPP Female | 27.53 |
| AA5913 | PHIS08H | PT8819 | 1/2" (12) Hosetail | 27.53 |

Flexible Connector



Anti Whip.

| Part No. | Description | Price £ |
|----------|------------------------------|------------|
| FE101 | 1/4" BSPT Male X BSPP Female | 10.32 |

Air Tool Whip Hose



BSPT Male.

| Part No. | Hose Length | Hose I/D (mm) | Thread Type | Price £ |
|----------|-------------|---------------|-----------------------------------|------------|
| HA2108 | 0.6m(2ft) | 7 | Standard Adaptor+1/4" BSPT Male | 6.61 |
| HA2109 | 0.6m(2ft) | 10 | Standard Adaptor+3/8" BSPT Male | 8.37 |
| HA2116 | 0.6m(2ft) | 13 | 100 Series Adaptor+1/2" BSPT Male | 10.44 |
| HA2132 | 0.6m(2ft) | 10 | XF Adaptor+1/4" BSPT Male | 10.44 |
| HA2149 | 0.6m(2ft) | 10 | Standard Adaptor+1/4" BSPT Male | 8.37 |

PCL Blowguns & Water Dispensers

Metal Blow Gun



BSPP Female Palm Grip With Safety Nozzle.

| Part No. | Description | Price £ |
|----------|-----------------|---------|
| BG106 | 1/4" BSPP Inlet | 10.25 |

Pistol Grip Blow Gun



BSPP Female Pistol Grip With Safety Nozzle.

| Part No. | Description | Price £ |
|----------|-----------------|---------|
| BG405 | 1/4" BSPP Inlet | 10.25 |

Plastic Blow Gun



BSPP Female - 100 mm Extended Nozzle.

| Part No. | Description | Price £ |
|----------|-----------------|---------|
| BG5002 | 1/4" BSPP Inlet | 7.30 |

Plastic Blow Gun



BSPP Female Safety Version.

| Part No. | Description | Price £ |
|----------|--------------------|---------|
| BG5004 | 1/4" BSPP Blow Gun | 7.90 |

Plastic Blow Gun



BSPP Female.

| Part No. | Description | Price £ |
|----------|---------------------|---------|
| BG5007 | 9" Extension Nozzle | 8.61 |

Plastic Blow Gun



BSPP Female - Low Noise Safety Version.

| Part No. | Description | Price £ |
|----------|--------------------------|---------|
| BG5006 | 1/4" BSPP Safety Blowgun | 17.37 |

Air & Water Gun



BSPP Female.

| Part No. | Description | Price £ |
|----------|-----------------------------|---------|
| AWG01 | Air and Water Jet Dispenser | 94.25 |

Water Dispenser



Designed to dispense water in such applications as a radiator or windscreen water bottle filler, PCL's Water Dispensers provide a simple solution. The sturdy design incorporates a lever for instant flow and cut-off.

| Part No. | Description | Price £ |
|----------|-----------------|---------|
| RF104 | Water Dispenser | 29.90 |

Safety Aircurtain Blow Gun



Safety Version.

| Part No. | Description | Price £ |
|----------|-------------------|---------|
| BG5005 | Safety Aircurtain | 10.00 |

see **section 1 & 18**
For More
Blowguns



PCL Tyre Inflation Equipment

Mk3 Tyre Inflator



European Standard 0-138lb/in² & 0-9.8bar - Guaranteed Accuracy - complies with BS EN 12645:1999 and EC Directive (86/217/EEC) - Faster Inflation - redesigned valve arrangement and larger bore hose allows for up to 30% faster inflation - Cast Aluminium Body With Impact Absorbing Rubber Bumper - Light (weighs less than 1kg) yet robust and durable Magnified Linear Scale - Accurate and easy to read anti-mist scale for inflation and deflation - Ergonomically Designed Trigger - Comfortable and easy to use with '2 click' action - Tested - Each unit has a unique serial number and is supplied with a Certificate of Calibration.

| Part No. | Description | Price £ |
|----------|---|------------|
| ALG3H03 | Twin Hold-on Hose (0.53m (21")) | 67.25 |
| ALG3H031 | Twin Hold-on Forecourt Model Hose (0.36m (14")) | 76.94 |
| ALG3H04 | Single Clip-on Connector Hose (0.53m (21")) | 65.96 |
| ALG3H05 | Twin Clip-on Tyre Shop Model Hose (1.8m (6")) | 89.50 |
| ALG3H06 | Twin Clip-on Tyre Shop Model Hose (2.7m (9")) | 90.91 |
| ALG3H061 | Single Clip-on Tyre Shop Model Hose (2.7m (9")) | 76.94 |

High Pressure Mk3 Tyre Inflator



Cast Aluminium Body With Impact Absorbing Rubber Bumper - Magnified Linear Scale - Accurate And Easy To Read - Anti-mist Scale For Inflation And Deflation - Ergonomically Designed Trigger - Comfortable And Easy To Use With "2 Click" Action - Available With Dual Scale Calibration Of 45-300lb/sq.in.

| Part No. | Hose Length | Connector Style | Price £ |
|----------|-------------|-----------------|------------|
| ALG5H04 | 1.8m (6ft) | Single Clip-on | 121.36 |
| ALG5H041 | 1.8m (6ft) | Twin Clip-on | 137.06 |

Alloy Tyre Inflator



PCL's Alloy Tyre Inflator is a general purpose tyre inflator with an all Alloy body with a rubber protected gauge. Simple and easy to use, they are ideal for general low volume tyre inflation - The ADTG4 Tyre Inflator has a durable alloy body and Euro style valve connector, and comes complete with operating instructions. Specifications: Reading Accuracy: 0.1bar / 2psi - Max Inlet Pressure: 15bar - Inlet thread: G 1/4

| Part No. | Description | Hose Length | Tyre Valve Connection | Calibration | Price £ |
|----------|---------------|-------------|-----------------------|--------------------------------------|------------|
| ADTG4 | Tyre Inflator | 0.85m | Euro clip-on | 10-210lb/in ² & 0.7-15bar | 34.35 |

Dial Type Tyre Inflator



Dial gauge accurate and easy to read - Surrounded in rubber for impact absorption.

| Part No. | Description | Price £ |
|----------|---|------------|
| DPG1H08 | European Standard 0-170lb/in ² in 2lb units & 0-12bar in 0.1bar units - Single Clip On | 20.78 |

Tyre Tread Depth Gauge



PCL Air Technology.

| Part No. | Description | Price £ |
|----------|------------------------|------------|
| TDG16C05 | Tyre Tread Depth Gauge | 3.96 |

Tyre Safety Pack



Comprising of a tyre pressure gauge and tyre depth gauge.

| Part No. | Description | Price £ |
|----------|---------------------------------|------------|
| TSP1T05 | Tyre Safety Pack (TPG1 + TDG16) | 14.25 |

Tyre Pressure Gauge-Angled Head Pocket Gauge



Incorporates a self-adjusting friction device which enables the pressure to be read when the gauge is removed from the valve - Integrated Pocket Clip - Protective Cap.

| Part No. | Description | Price £ |
|----------|---|------------|
| TPG1H01 | European Standard-6-50 lbf/in ² in 1lb units & 0.5-3.4 bar in 0.1 bar unit | 5.13 |

Digital Hand Held Tyre Inflator



Key Features: Easy To read Digital Display - Ceramic Sensor - Light Weight and Shock Resistant - Straight Through Valve Design - Individually Tested and Certified - bar, lbf/in², kPa Versions Available - Key Benefits: Easy To Use With Clear, Consistent Accuracy and Safety - Robust With Low Life Time Costs, Fast Inflation, Reducing Operational Costs - Guaranteed Accuracy - Highly Versatile - Max - Pressure: 12 bar - Max - Temp - 20 to 60°C

| Part No. | Description | Price £ |
|----------|--|------------|
| DAC1A03 | 21 INCH HOSE - TWIN HOLD ON CONNECTOR | 89.25 |
| DAC1C08 | 6' HOSE - EURO CONNECTOR | 78.75 |
| DAC1A06 | 2.7M (9FT) HOSE WITH CLIP ON CONNECTOR | 99.75 |

Analogue Hand Held Tyre Inflator



PCL Air Technology: Key Features: Dial Display - Ceramic Sensor - Shock Resistant - Straight Through Valve Design - Individually Tested and Certified - bar, lbf/in², kPa Versions Available - Simple To Use - Consistent Accuracy and Safety - Long Life With Low Life Time Costs - Fast Inflation, Reducing Operational Costs - Guaranteed Accuracy - Highly Versatile - Max - Pressure: 12 bar - Max - Temp - 20 to 60°C

| Part No. | Description | Price £ |
|----------|--|------------|
| AFG1H03 | 21 INCH HOSE - TWIN HOLD-ON CONNECTOR | 63.00 |
| AFG1H08 | 6' HOSE - EURO CONNECTOR | 52.50 |
| AFG1H06 | 2.7 (9FT) HOSE WITH TWIN CLIP ON CONNECTOR | 73.50 |

Tyre Valve Connector



1/4 Inlet BSPP Female Thread - European Standard 0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|-----------------------|----------|---------|
| CO1A03 | Twin Hold On | Open End | 10.58 |

Tyre Valve Connector



1/4 Inlet BSPP Female Thread - European Standard 0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|-----------------------|------------|---------|
| CO1B03 | Twin Hold On | Closed End | 10.57 |

Tyre Valve Connector



Hose ID 1/4 (6.35mm) - European Standard 0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|-----------------------|----------|---------|
| CO2H03 | Single Clip On | Open End | 6.42 |

Tyre Valve Connector



Hose ID 1/4 (6.35mm) - European Standard
0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|-----------------------|------------|---------|
| CO2J03 | Single Clip On | Closed End | 6.42 |

Tyre Valve Connector



1/4 Inlet BSPP Female Thread - European Standard
0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|-----------------------|----------|---------|
| CO3A03 | Twin Clip On | Open End | 24.31 |

Tyre Valve Connector



1/4 Inlet BSPP Female Thread European Standard
0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|-----------------------|------------|---------|
| CO3B03 | Twin Clip On | Closed End | 24.31 |

Tyre Valve Connector



Hose ID 3/6 (4.75mm) - European Standard
0-138lb/in² & 0-9.8bar

| Part No. | Valve Connection Type | Style | Price £ |
|----------|---------------------------|----------|---------|
| CO8E72 | Euro Style Single Clip On | Open End | 4.77 |

12V Impact Wrench



Change your car wheels effortlessly, no matter where you are - Plugs directly into a cigarette lighter (or clamps to your car battery) - Forward and reverse operation - Automatic work light - Supplied in a strong protective case complete with 4 socket sizes and wheel trim remover.

| Part No. | Description | Price £ |
|----------|-------------------|---------|
| ATT607 | 12V Impact Wrench | 36.00 |

Tyre Valve Cores



Suitable For Standard Tyre Valves - Resistant To Petrol, Oil and Other Contaminants - Price is per pack

| Part No. | Description | Qty Per Pack | Price £ |
|----------|-------------------|--------------|---------|
| TA02/M | Short Valve Cores | 4 | 2.08 |
| TA09/M | Long Valve Cores | 4 | 2.08 |

Tyre Valve Tool



PCL Air Technology


| Part No. | Description | Price £ |
|----------|---------------------|---------|
| TVT05 | Tyre Valve Tool SKP | 2.15 |

Tyre Valve Caps



Domed Dust Caps For Standard Tyre Valves - Price is per pack

| Part No. | Description | Qty Per Pack | Price £ |
|----------|------------------|--------------|---------|
| TA37/M | Plastic Dust Cap | 5 | 0.99 |
| TA44/M | Metal Dust Cap | 5 | 2.08 |



See Section 1 For Parker Legris Transair

DTDG1D04 DIGITAL DEPTH GAUGE



PCL Made from extra strong carbon fibre composite - Large LCD display - Zero setting in any position - Metric, decimal inch and fraction inch (1/64) toggle - 1 battery - SR44 1.5v(supplied).

| Part No. | Price £ |
|----------|---------|
| DTDG1D04 | 12.95 |

12V 3-in 1 Tyre Inflator



12v air compressor is suitable for cars, vans, 4X4 Vehicles vans and jeeps and features a convenient work light and flashing hazard warning light - Airbed, Cycle and ball Adaptors included - Maximum Pressure 150lbf/in² - Built-in work and flashing hazard warning light - Features handy storage compartment for cables - air hose and accessories.

| Part No. | Description | Price £ |
|----------|--------------------------|---------|
| ATT741 | 12V 3-in 1 Tyre Inflator | 24.00 |

Tyre Valve Extensions



Extensions Allow easier Access To Tyre Valve For Inflation And Deflation - Price is per pack

| Part No. | Description | Qty Per Pack | Price £ |
|----------|------------------|--------------|---------|
| TA30/M | 31.5mm Extension | 4 | 4.57 |
| TA16/M | 37.5mm Extension | 4 | 5.08 |
| TA23/M | 19mm Extension | 4 | 4.02 |

PCL Air Tools

Air Vacuum Cleaner



Garage Model: Dust Bag, Nozzle suction head Included - Has blow facility - Spark-free alloy body makes ideal for use in flameproof areas - Safety nozzle prevents blow back of dust - Industrial Model: Dust Bag, Nozzle suction head Included - Has blow facility - Spark-free alloy body makes ideal for use in flameproof areas - Safety nozzle prevents blow back of dust - 1.8m(6ft) of flexi-tube, suction nozzle and 8mm bore hose tailpiece included - Suitable for large volumes of debris.

| Part No. | Description | Price £ |
|----------|-------------------------|---------|
| AV101 | Airvac-Garage Model | 84.64 |
| AV201 | Airvac-Industrial Model | 106.00 |

1/2" Impact Wrench (Composite Body)



Twin Hammer Mechanism - Forward And Reverse Mode - Rear Exhaust Through Handle - 4 Forward Operation Impact Settings - Non-slip Warm Comfortable Grip - Progressive Throttle - Positive Trigger Action (allows variable speed).

| Part No. | Square Drive | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Torque (@90psi) | Price £ |
|----------|--------------|-------------|---------------|------------|-----------------|---------|
| APT233 | 1/2" | 2.65 | 1/4" | 10mm | 700 Nm | 151.35 |

10mm Drill



Triple Planetary Gear System - Jacobs Keyless Chuck - Rear Exhaust Through Handle - Powerful Air Motor - Positive Trigger Action.

| Part No. | Chuck Size | Weight (Kg) | Air Inlet BSP | Free Speed | Price £ |
|----------|-------------|-------------|---------------|------------|---------|
| APT401 | 3/8" (10mm) | 1.2 | 1/4" | 2200 RPM | 56.19 |

10mm Reversible Drill



Triple Planetary Gear System - Jacobs Keyless Chuck - Rear Exhaust Through Handle - Powerful Air Motor - Positive Trigger Action - Side Mounted Forward / Reverse Shift - Ideal For Drilling, Reaming and Honing.

| Part No. | Chuck Size | Weight (Kg) | Air Inlet BSP | Free Speed | Price £ |
|----------|-------------|-------------|---------------|------------|---------|
| APT401R | 3/8" (10mm) | 1.1 | 1/4" | 1800 RPM | 63.06 |

1/2" Impact Wrench



General Purpose Impact Wrench - Forward And Reverse Mode - Rear Exhaust - 4 Forward Operation - Impact Settings - Non-slip Comfortable Grip - Single Handed Direction Change - Positive Trigger Action (allows variable speed).

| Part No. | Square Drive | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Torque (@90psi) | Price £ |
|----------|--------------|-------------|---------------|------------|-----------------|---------|
| APT205 | 1/2" | 2 | 1/4" | 10mm | 540 Nm | 104.17 |

3/4" Impact Wrench



Pin Clutch Hammer Mechanism - Forward And Reverse Mode - 3 Fwd & 3 Rev Operating Impact Settings - Rear Exhaust Through Handle - Non-slip Comfortable Grip - Single Handed Direction Change - Ideal For Truck, Bus and Farm Machinery Work.

| Part No. | Square Drive | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Torque (@90psi) | Price £ |
|----------|--------------|-------------|---------------|------------|-----------------|---------|
| APT230 | 3/4" | 5.2 | 3/8" | 13mm | 1350 Nm | 320.42 |

Screw Driver



Maximum Torque 17Nm - Spring Compression Determines Torque Setting - Rear Exhaust Through Handle - Sensitive Trigger Mechanism - Convenient Forward / Reverse Shift - Ideal For General Workshops and Bodyshops.

| Part No. | Chuck Size | Weight (Kg) | Air Inlet BSP | Free Speed | Price £ |
|----------|------------|-------------|---------------|------------|---------|
| APT407 | 1/4" (Hex) | 1.1 | 1/4" | 1800 RPM | 104.17 |

1" Impact Wrench (With Extended Shank)



Powerful Heavy Duty Wrench - Twin Hammer Mechanism - 200mm Extended Shank - One Knob Combining Power Regulation and Forward/Reverse Shift - Rear Exhaust Through Handle - 3 Forward Operating Impact Settings - Side Handle For Comfortable Grip.

| Part No. | Square Drive | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Torque (@90psi) | Price £ |
|----------|--------------|-------------|---------------|------------|-----------------|---------|
| APT263 | 1" | 10.6 | 3/8" | 13mm | 2445 Nm | 639.52 |

Die Grinder



6mm Collet (3 Piece Design) - High Velocity, Low Vibration - Rear Exhaust Through Handle - Safety Throttle Lever - Excellent For Tyre Buffing, Polishing and Grinding - Very Versatile, Excellent In Confined Workspaces.

| Part No. | Collet Size | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Free Speed | Price £ |
|----------|-------------|-------------|---------------|------------|------------|---------|
| APT702 | 6mm | 0.6 | 1/4" | 10mm | 22000rpm | 33.25 |

Belt Sander



Optimal Positioning Due To Rotating Handle - Rear Exhaust Through Handle - Adjustable Sanding Arm - Mechanism For Quick and Easy Belt Exchange - Universal Belt Size - Maximum Belt Speed 16.5m/s.

| Part No. | Stroke (Orbit) | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Free Speed | Price £ |
|----------|----------------|-------------|---------------|------------|------------|---------|
| APT755 | 25mm | 0.8 | 1/4" | 10mm | 16000rpm | 118.67 |



Also See Section 24/8 & 24/24 for Further Ranges Of Air Tools & Accessories



Palm Sander



For Industry, Car Body paint Shops and Craftsmen - Precision Air Motor With Extreme High Torque - Central Vacuum Model With Universal Attachment - Optimal Direct Connection For Dust Extraction - Speed Regulator and Insulated Handle - Includes 150mm Velcro Backing Pad - Rear Exhaust.

| Part No. | Stroke (Orbit) | Weight (Kg) | Air Inlet BSP | Pad Size | Free Speed | Price £ |
|----------|----------------|-------------|---------------|----------|------------|---------|
| APT768 | 8mm | 0.8 | 1/4" | 150mm | 10000rpm | 170.85 |

3/8" Ratchet



Forward / Reverse Knob On The Ratchet Head - Ball Type Retainer Easy Forward / Reverse Shift - Progressive Throttle.

| Part No. | Square Drive | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Torque (@90psi) | Price £ |
|----------|--------------|-------------|---------------|------------|-----------------|---------|
| APT320 | 3/8" | 1.2 | 1/4" | 10mm | 60Nm | 38.99 |

Body Saw



Ideal For Bodyshop and Metal Workshops - Insulated Handle and Anti Vibration Cover - 10mm Max - Stroke with Adjustable Blade Guide - Safety Throttle Lever - Suitable For Universal Blades.

| Part No. | Cutting Capacity | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Free Speed | Price £ |
|----------|------------------|-------------|---------------|------------|------------|---------|
| APT650 | 16swg | 0.75 | 1/4" | 10mm | 9000rpm | 104.17 |

Mini Cut Off Tool



Ideal For Light Cutting Tasks - Rear Exhaust Through Handle - For Disks Up To 75mm Diameter (10mm Thick) - Positive Throttle Action With Safety Feature - Metal Safety Guard - Excellent In Confined Workspaces.

| Part No. | Disk Size (mm) | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Free Speed | Price £ |
|----------|----------------|-------------|---------------|------------|------------|---------|
| APT719 | 10x75 | 1 | 1/4" | 10mm | 20000rpm | 46.15 |

Orbital Sander



Two Handed Operation - Built In Speed Regulator - Rear Exhaust - Insulated Handle and Motor Housing - Random Orbit - Positive Lever Action - Includes 150 Diameter Backing Pad For Self-adhesive Abrasives.

| Part No. | Stroke (Orbit) | Weight (Kg) | Air Inlet BSP | Pad Size | Free Speed | Price £ |
|----------|----------------|-------------|---------------|----------|------------|---------|
| APT720 | 8mm | 1.5 | 1/4" | 150mm | 10000rpm | 51.43 |

Air Hammer



General Purpose - Ideal For Body Shop, Rust Removal Etc - 4500 Blows Per Minute - 10-11mm Shank Opening - Rear Exhaust Through Handle - Coiled Spring Chisel Retainer - Positive Action Trigger.

| Part No. | Stroke Length | Weight (Kg) | Air Inlet BSP | Min Hose Ø | Speed | Price £ |
|----------|---------------|-------------|---------------|------------|---------|---------|
| APT517 | 3mm | 1.6 | 1/4" | 10mm | 4500bpm | 48.78 |

Needle Scaler



Ideal For Surface Preparation - 4000 Blows Per Minute - Rugged Design - Straight Handle - Positive Lever Action - Hardened Self-adjusting Needles.

| Part No. | Needle Ø | Weight (Kg) | Air Inlet BSP | No - Of Needles | Free Speed | Price £ |
|----------|----------|-------------|---------------|-----------------|------------|---------|
| APT561 | 3" | 1.3 | 1/4" | 12 | 4000bpm | 100.09 |

Grease Gun



Pistol Grip and Single Pulse Trigger Operated - Grease Loads Easily With Standard 14oz Cartridge - Grease Applied Under Steady Pressure - Angled Design With Die Cast Body and Head - Bulk Or Manual Fill.

| Part No. | Cartridge Load | Bulk Load | Weight | Air Inlet BSP | Min - Hose Ø | Price £ |
|----------|----------------|-----------|--------|---------------|--------------|---------|
| APT813 | 14oz | 400cc | 1.75kg | 1/4" | 10mm | 48.78 |

PCL Spray Equipment

D.I.Y Suction Spray Gun



For General Purpose & DIY Use - 1.4mm Fluid Nozzle 1litre Cup Capacity Air Consumption: 5cfm (150 ltr/min.).

| Part No. | Description | Price £ |
|----------|-------------------------|---------|
| SG01D | D.I.Y Suction Spray Gun | 21.79 |

D.I.Y Gravity Spray Gun



For General Purpose & DIY Use - 1.5mm Fluid Nozzle - 0.5 litre Cup Capacity - Air Consumption: 7cfm (198 ltr/min.).

| Part No. | Description | Price £ |
|----------|-------------------------|---------|
| SG02D | D.I.Y Gravity Spray Gun | 23.97 |

5 Piece Nylon Accessory Kit



Paint Spray Gun - Paraffin Gun - Tyre Inflator - Blow Gun - Coiled Hose - Material: Nylon

| Part No. | Description | Price £ |
|----------|-------------------|---------|
| AK015P | 5 Piece Nylon Kit | 35.08 |

Economy Gravity Spray Gun



For General Purpose & DIY Use - 1.5mm Fluid Nozzle - 0.5 litre Cup Capacity - Air Consumption: 7cfm (198 ltr/min.).

| Part No. | Description | Price £ |
|----------|-----------------------|---------|
| SG02E | Economy Spray Gun (G) | 38.17 |

Economy Suction Spray Gun



For General Purpose & DIY Use - 1.4mm Fluid Nozzle - 1litre Cup Capacity - Air Consumption: 5cfm (150 ltr/min.).

| Part No. | Description | Price £ |
|----------|-----------------------|---------|
| SG01E | Economy Spray Gun (S) | 40.35 |

5 Piece Metal Accessory Kit



Paint Spray Gun - Paraffin Gun - Tyre Inflator - Blow Gun - Coiled Hose - Material: Metal.

| Part No. | Description | Price £ |
|----------|-------------------|---------|
| AK015M | 5 Piece Metal Kit | 45.05 |

HVLP Suction Spray Gun



Fully Adjustable - 1.7mm Fluid Nozzle - 0.5 litre Cup Capacity - 10" Fan Width - Air Consumption: 7cfm (198 ltr/min.).

| Part No. | Description | Price £ |
|----------|-------------------|------------|
| SG01P | Suction Spray Gun | 47.20 |

HVLP Gravity Spray Gun



Compliant Spray Gun - Aircap With ECO & T System - Allows User To Work With A Low Pressure, Obtaining A Transfer Of Above 65% - Fully Adjustable - 1.78mm Fluid Nozzle - 0.75 litre Cup Capacity - Suitable For Most Applications - Air Consumption: 6.5cfm (180 ltr/min.).

| Part No. | Description | Price £ |
|----------|-------------------|------------|
| SG02P | Gravity Spray Gun | 47.20 |

Sand Blast Gun



1Litre Container - Air Consumption: 6.5cfm (184 ltr/min.).

| Part No. | Description | Price £ |
|----------|----------------|------------|
| SBG1 | Sand Blast Gun | 14.14 |

Paraffin Gun



Adjustable Nozzle - 1Litre Steel Container - Air Consumption: 7cfm (198 ltr/min.).

| Part No. | Description | Price £ |
|----------|--------------|------------|
| PSG1 | Paraffin Gun | 11.96 |

PCL Air Treatment

Filter Regulator & Lubricator



Wall Bracket and Gauge Included - Locking Device - Protective Metal Casing.

| Part No. | Drain | Port Thread BSPP | Filtration Micron | Regulating Pressure (bar) | Maximum Inlet Pressure (bar) | Price £ |
|----------|-----------------------|------------------|-------------------|---------------------------|------------------------------|------------|
| ATCFRL6 | Manual/Semi-Automatic | 1/4" | 10 | 0-10 | 12 | 47.70 |
| ATCFRL12 | Manual/Semi-Automatic | 1/2" | 10 | 0-12 | 16 | 65.21 |



**See Section 1 & 22 For
Further Ranges Of Filters,
Regulators & Lubricators**



Filter Regulators



Wall Bracket and Gauge Included - Locking Device - Metal Casing.

| Part No. | Drain | Port Thread BSPP | Filtration Micron | Regulating Pressure (bar) | Maximum Inlet Pressure (bar) | Price £ |
|----------|-----------------------|------------------|-------------------|---------------------------|------------------------------|------------|
| ATC6 | Manual/Semi-Automatic | 1/4" | 10 | 0-10 | 12 | 27.17 |
| ATC12 | Manual/Semi-Automatic | 1/2" | 10 | 0-12 | 16 | 38.64 |

Regulators



Wall Bracket and Gauge Included - Locking Device - Protective Metal Casing.

| Part No. | Port Thread BSPP | Regulating Pressure | Maximum Inlet Pressure (bar) | Price £ |
|----------|------------------|---------------------|------------------------------|------------|
| ATR6 | 1/4" | 0-10 | 12 | 16.31 |
| ATR12 | 1/2" | 0-12 | 16 | 25.36 |

Filters



Wall Bracket and Gauge Included - Protective Metal Casing.

| Part No. | Drain | Port Thread BSPP | Filtration Micron | Maximum Inlet Pressure (bar) | Price £ |
|----------|-----------------------|------------------|-------------------|------------------------------|------------|
| ATF6 | Manual/Semi-Automatic | 1/4" | 10 | 12 | 19.93 |
| ATF12 | Manual/Semi-Automatic | 1/2" | 10 | 16 | 27.77 |



For a range of top quality **accessories** see **section 18**

Lubricators



Wall hanging Bracket Included - Fully adjustable oil flow - Easy-fill aperture - Protective Metal Casing.

| Part No. | Port Thread BSPP | Maximum Inlet Pressure (bar) | Price £ |
|----------|------------------|------------------------------|------------|
| ATL6 | 1/4" | 12 | 20.53 |
| ATL12 | 1/2" | 14 | 27.77 |



PCL Prestige Air Tools



APP101 3/8" Impact Wrench



PCL PRESTIGE RANGE - Ergonomic and streamlined housing for greater access in tight spaces - Soft grip provides comfort for prolonged usage - Handle exhaust to direct air away from work piece and operator - Energy efficient motor for maximum Performance - Swivel air inlet to prevent hose twist - Magnesium body for lighter weight - Max Torque 200ft-lb 271nm - Min Hose Size 3/8 10mm - Average Air Consumption 2.7cfm 75l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|-------------|-------------------|-------------------------------|-----------|------------|
| APP101 | 3/8" | Twin Hammer | 10000 | 2.01 | 92.8 | 149.00 |

APP201 1/2" Impact Wrench



PCL PRESTIGE RANGE - Ergonomic and streamlined housing for greater access in tight spaces - Soft grip provides comfort for prolonged usage - Handle exhaust to direct air away from work piece and operator - Energy efficient motor for maximum Performance - Swivel air inlet to prevent hose twist - Magnesium body for lighter weight - Max Torque 320ft-lb 433nm - Min Hose Size 3/8 10mm - Average Air Consumption 2.7cfm 75l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|-------------|-------------------|-------------------------------|-----------|------------|
| APP201 | 1/2" | Twin Hammer | 10000 | 2.01 | 92.8 | 165.40 |

APP203 1/2" Impact Wrench (Composite)



PCL PRESTIGE RANGE - Composite housing making it lightweight and strong - Even balance with a compact profile - Soft grip provides comfort for prolonged usage - Handle exhaust to direct air away from work piece and operator - Energy efficient motor for maximum performance and long life - Swivel air inlet to prevent hose twist - Twin hammer mechanism provides more power and smooth balanced blows - Max Torque 510ft-lb 690nm - Min Hose Size 3/8 10mm - Average Air Consumption 4.7cfm 133l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|-------------|-------------------|-------------------------------|-----------|------------|
| APP203 | 1/2" | Twin Hammer | 8500 | 4.5 | 100 | 208.75 |

APP234 3/4" Impact Wrench



PCL PRESTIGE RANGE - Ergonomic housing Design - Soft grip provides comfort for prolonged usage - Handle exhaust to direct air away from work piece and operator - Energy efficient motor for maximum performance and long life - Swivel air inlet to prevent hose twist - Twin hammer mechanism provides more power and smooth balanced blows - Max Torque 1100ft-lb 1490nm - Min Hose Size 1/2 13mm - Average Air Consumption 7.2cfm 204l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|-------------|-------------------|-------------------------------|-----------|------------|
| APP234 | 3/4" | Twin Hammer | 5500 | 2.64 | 95.3 | 429.00 |

APP270 1" Impact Wrench



PCL PRESTIGE RANGE - Ergonomic housing Design - Side mounted handle for better operator control - Magnesium body making unit very lightweight - Energy efficient motor for maximum performance and long life - Low vibration allowing longer working time - Max Torque 1600ft-lb 2169nm - Min Hose Size 3/4 19mm - Average Air Consumption 7.9cfm 224l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|-------------|----------------|----------------------------|-----------|---------|
| APP270 | 1" | Twin Hammer | 4500 | 2.35 | 94 | 757.80 |

APP310 3/8" Ratchet



PCL PRESTIGE RANGE - Optimised gear ratio and air flow for extra performance - Advanced and durable head design for longer life - Fast run down to speed up tightening operations - Soft grip provides superior comfort - Max Torque 70ft-lb 95nm - Min Hose Size 3/8 10mm - Average Air Consumption 2.6cfm 73.6l/min - Operating Pressure 90PSI

| Part No. | Drive | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|----------------|----------------------------|-----------|---------|
| APP310 | 3/8" | 160 | 1.13 | 91.6 | 97.90 |

APP500SET Heavy Duty Air Hammer Set



PCL PRESTIGE RANGE - T-Handle ergonomic design to achieve overall balance reducing fatigue - Patented shock reduction device - One piece over moulded grip for comfort and anti skipping - Swivel inlet to prevent hose twist - Quick change retainer for simple accessory change - Complete with selection of chisels in blow moulded carry case - Min Hose Size 3/8 10mm - Average Air Consumption 2.73cfm 5.35l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|-----------|-------------|----------------|----------------------------|-----------|---------|
| APP500SET | 67mm Stroke | 2900 | 5.35 | 102 | 131.80 |

APP600 Air Body Saw



PCL PRESTIGE RANGE - High cutting capacity - Lightweight design to reduce fatigue - Swivel inlet to prevent hose twist - Soft grip provides superior comfort and non slip operation - Min Hose Size 3/8 10mm - Average Air Consumption 1.24cfm 35.1l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-----------------------|----------------|----------------------------|-----------|---------|
| APP600 | 25mm Cutting Capacity | 10000 | 3 | 83.5 | 165.30 |

APP700SET Die Grinder Set



PCL PRESTIGE RANGE - Ergonomic and streamlined composite housing for comfort and balance - Ductile ironed cylinder for high strength and long life - Safety throttle to prevent accidental start ups - Rear exhaust to direct air away from work piece - Complete with selection of accessories in blow moulded case - Min Hose Size 3/8 10mm - Average Air Consumption 4cfm 113l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|-----------|-------|-----------|----------------|----------------------------|-----------|---------|
| APP700SET | 6mm | 0.43 HP | 20000 | 2.42 | 86.5 | 87.25 |

APP708 Mini Cut off Tool



PCL PRESTIGE RANGE - High cutting capacity - Lightweight design to reduce fatigue - Double bearing spindle for increased life - Soft grip provides superior comfort and non slip operation - Speed regulator for accurate operation - Min Hose Size 3/8 10mm - Average Air Consumption 3cfm 85l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|--------------------|----------------|----------------------------|-----------|---------|
| APP708 | 75mm Disc Diameter | 21000 | 0.52 | 85 | 71.80 |

APP760 Palm Sander



PCL PRESTIGE RANGE - 12,000rpm for swirl free finishes - Durable composite design - Built in power regulator for optimised power control - Well balanced for smooth handling - Central vacuum exhaust - Min Hose Size 3/8 10mm - Average Air Consumption 2.5cfm 70.6l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|----------------------|----------------|----------------------------|-----------|---------|
| APP760 | 6" Pad and 5mm Orbit | 12000 | 2.8 | 85 | 160.00 |

PCL Air Tools

APT105 3/8" Impact Wrench



PCL AIR TOOLS - General purpose wrench - Single hammer mechanism - Forward and reverse model - Handle exhaust - Max Torque 100ft-lb 135nm - Min Hose Size 3/8 10mm - Average Air Consumption 3cfm 70.6l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|---------------|----------------|----------------------------|-----------|---------|
| APT105 | 3/8" | Single Hammer | 9000 | 3.4 | 80 | 83.55 |

APT265 1" Impact Wrench (pistol grip)



PCL AIR TOOLS - Twin hammer mechanism - 2,430Nm torque - Side handle for operator comfort - Great durability and power - Max Torque 1800ft-lb 2445nm - Min Hose Size 1/2 13mm - Average Air Consumption 11cfm 317l/min - Operating Pressure 90PSI

| Part No. | Drive | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|-------------|----------------|----------------------------|-----------|---------|
| APT265 | 1" | Twin Hammer | 4000 | 17.7 | 103.7 | 660.20 |

APT330 1/2" Ratchet



PCL AIR TOOLS - Ball type retainer - Progressive throttle - Forward/reverse knob on ratchet head - Accommodates larger socket range - Max Torque 45ft-lb 60nm - Min Hose Size 3/8 10mm - Average Air Consumption 3.6cfm 101l/min - Operating Pressure 90PSI

| Part No. | Drive | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-------|----------------|----------------------------|-----------|---------|
| APT330 | 1/2" | 150 | 5.2 | 90 | 60.50 |

APT402 10mm Angle Drill



PCL AIR TOOLS - Angle head for easy access - Rear exhaust - Progressive throttle - Powerful air motor - Min Hose Size 3/8 10mm - Average Air Consumption 4cfm 113l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|------------|----------------|----------------------------|-----------|---------|
| APT402 | 10mm Chuck | 1700 | 1.5 | 87 | 104.40 |



See Section 24/23 for Our Range Of
Universal Air Tools & Accessories



APT408 Straight Screwdriver



PCL AIR TOOLS - High torque - Rear exhaust through handle - Spring compression determines torque setting - Sensitive trigger mechanism - Min Hose Size 3/8 10mm - Average Air Consumption 4cfm 113l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-----------|----------------|----------------------------|-----------|---------|
| APT408 | 1/4" Hex | 1700 | 4.6 | 86 | 104.40 |

APT715 4" Angle Grinder



PCL AIR TOOLS - Powerful Motor - Side handle for operator comfort - Excellent performance and durability - 4" cutting disc - Min Hose Size 3/8 10mm - Average Air Consumption 4.8cfm 136l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|---------------------|----------------|----------------------------|-----------|---------|
| APT715 | 100mm Disc Diameter | 12000 | 4.18 | 86 | 215.00 |

APT716 7" Angle Grinder



PCL AIR TOOLS - Powerful Motor - Side handle for operator comfort - Excellent performance and durability - 7" cutting disc - Min Hose Size 3/8 10mm - Average Air Consumption 5.3cfm 149l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|---------------------|----------------|----------------------------|-----------|---------|
| APT716 | 180mm Disc Diameter | 7600 | 3.3 | 93 | 328.90 |

APT660 Nibbler



PCL AIR TOOLS - Push cutting operation - Ideal for tight spaces and intricate shapes - Quick change punch and die - Powerful Motor - Min Hose Size 3/8 10mm - Average Air Consumption 9.9cfm 280l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|-----------|----------------|----------------------------|-----------|---------|
| APT660 | Push Cut | 2500 | 4.1 | 91.2 | 66.40 |

APT670 Shear



PCL AIR TOOLS - Ergonomic handle for operator comfort - Long life and reliable cutting - Handle exhaust - Fast cutting action - Min Hose Size 3/8 10mm - Average Air Consumption 4cfm 113l/min - Operating Pressure 90PSI

| Part No. | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|----------------|----------------------------|-----------|---------|
| APT670 | 2000 | 4.1 | 86.7 | 66.40 |

APT756 20mm Belt Sander



PCL AIR TOOLS - Optimal positioning due to rotating handle - Rear exhaust through handle - Adjustable sanding arm - Mechanism for quick and easy belt change - Min Hose Size 3/8 10mm - Average Air Consumption 2.5cfm 70l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Free Speed RPM | Vibration m/s ² | Sound DbA | Price £ |
|----------|---------------|----------------|----------------------------|-----------|---------|
| APT756 | Belt 20x480mm | 16000 | 2.4 | 78 | 175.70 |

APT690 Riveter



PCL AIR TOOLS - Ergonomic design for operator comfort - Lightweight - 3/16 Max - capacity - Min Hose Size 3/8 10mm - Average Air Consumption 4cfm 113l/min - Operating Pressure 90PSI

| Part No. | Mechanism | Vibration m/s ² | Price £ |
|----------|---------------------|----------------------------|---------|
| APT690 | 1870 Traction Power | 1.3 | 98.10 |

APT32 5pc Saw Blade Set



PCL AIR TOOLS - Suitable for use with PCL and other brand body saws - Excellent performance - Universal fitment - Fast clean cutting action.

| Part No. | Price £ |
|----------|---------|
| APT32 | 12.05 |

APT75FCM 10 Cutting Discs



PCL AIR TOOLS - Suitable for use with PCL and other brand cut off tools - 75mm diameter - Excellent performance and life - 10mm bore.

| Part No. | Price £ |
|----------|---------|
| APT75FCM | 16.25 |

APT90A Self Adhesive Pad



PCL AIR TOOLS - For use with self adhesive sanding papers - 6" diameter - Excellent durability and balance - Std 5/16 thread.

| Part No. | Price £ |
|----------|---------|
| APT90A | 23.30 |

APT90V Velcro Pad



PCL AIR TOOLS - For use with Velcro sanding papers 6" diameter - Excellent durability and balance - Std 5/16 thread.

| Part No. | Price £ |
|----------|---------|
| APT90V | 23.30 |

APT10 10pc Impact Socket Set



PCL AIR TOOLS - Use for general assembly, maintenance and fastening - Suitable for use with 1/2 square drive - 10 piece metric impact sockets - Chrome vanadium for longer life

| Part No. | Price £ |
|----------|---------|
| APT10 | 23.00 |

APT15 3pc Alloy Wheel Impact Socket Set



PCL AIR TOOLS - Chrome molybdenum sockets - Suitable for use with 1/2 square drive - 3 piece metric impact sockets - Socket sizes 17,19 & 21mm.

| Part No. | Price £ |
|----------|---------|
| APT15 | 23.00 |

APT20 5pc Chisel Set



PCL AIR TOOLS - Suitable for use with PCL and other brand air hammers - Supplied in a tool roll - Chisel shank size .401 Parker Taper - Chrome Moly forged for longer life.

| Part No. | Price £ |
|----------|---------|
| APT20 | 18.40 |

PCL Air Tool Hose

Air Tool Hose Standard Adaptor & BSPT 1/4" Male Ends



PCL AIR TOOL HOSE - Excellent abrasion resistance - Good flexibility and kink resistant - Resistance to oil and fuels - Silicone free.

| Part No. | Hose Length | Hose ID | Fittings | Price £ |
|----------|-------------|---------|------------------------------------|---------|
| HA2112 | 10m | 5/16" | Standard Adaptors & 1/4" BSPT Male | 48.60 |
| HA2113 | 20m | 5/16" | Standard Adaptors & 1/4" BSPT Male | 84.56 |
| RHA2036 | 10m | 10mm | Standard Adaptors & 1/4" BSPT Male | 52.83 |
| RHA2037 | 20m | 10mm | Standard Adaptors & 1/4" BSPT Male | 90.41 |

Air Tool Hose 100 Series Adaptor & BSPT 1/2" Male Ends



PCL AIR TOOL HOSE - Excellent abrasion resistance - Good flexibility and kink resistant - Resistance to oil and fuels - Silicone free.

| Part No. | Hose Length | Hose ID | Fittings | Price £ |
|----------|-------------|---------|--------------------------------------|---------|
| HA2110 | 10m | 13mm | 100 Series Adaptors & 1/2" BSPT Male | 75.09 |
| HA2111 | 20m | 13mm | 100 Series Adaptors & 1/2" BSPT Male | 134.33 |

Air Tool Hose Vertex Coupling & Standard Adaptor Ends



PCL AIR TOOL HOSE - Excellent abrasion resistance - Good flexibility and kink resistant - Resistance to oil and fuels - Silicone free.


| Part No. | Hose Length | Hose ID | Fittings | Price £ |
|----------|-------------|---------|------------------------------------|---------|
| HA2135 | 5m | 8mm | Standard Adaptor & Vertex Coupling | 32.22 |
| HA2125 | 10m | 8mm | Standard Adaptor & Vertex Coupling | 50.25 |
| HA2137 | 15m | 8mm | Standard Adaptor & Vertex Coupling | 68.18 |
| HA2138 | 20m | 8mm | Standard Adaptor & Vertex Coupling | 86.21 |
| HA2133 | 5m | 10mm | Standard Adaptor & Vertex Coupling | 35.96 |
| HA2134 | 10m | 10mm | Standard Adaptor & Vertex Coupling | 52.50 |
| HA2139 | 15m | 10mm | Standard Adaptor & Vertex Coupling | 72.96 |
| HA2129 | 20m | 10mm | Standard Adaptor & Vertex Coupling | 92.04 |

Air Tool Hose 100 Series Coupling & Adaptor Ends



PCL AIR TOOL HOSE - Excellent abrasion resistance - Good flexibility and kink resistant - Resistance to oil and fuels - Silicone free.


| Part No. | Hose Length | Hose ID | Fittings | Price £ |
|----------|-------------|---------|-------------------------------|---------|
| HA2144 | 10m | 13mm | 100 Series Adaptor & Coupling | 88.79 |
| HA2150 | 15m | 13mm | 100 Series Adaptor & Coupling | 118.22 |
| HA2128 | 20m | 13mm | 100 Series Adaptor & Coupling | 147.47 |
| HA2152 | 30m | 13mm | 100 Series Adaptor & Coupling | 206.15 |



For

Valves

see Section 20



Air Tool Hose XF Coupling & Adaptor Ends



PCL AIR TOOL HOSE - Excellent abrasion resistance - Good flexibility and kink resistant - Resistance to oil and fuels - Silicone free.

| Part No. | Hose Length | Hose ID | Fittings | Price £ |
|----------|-------------|---------|-----------------------|------------|
| HA2140 | 5m | 10mm | XF Adaptor & Coupling | 40.17 |
| HA2141 | 10m | 10mm | XF Adaptor & Coupling | 58.67 |
| HA2142 | 15m | 10mm | XF Adaptor & Coupling | 77.18 |
| HA2143 | 20m | 10mm | XF Adaptor & Coupling | 96.27 |



Universal Air Tools



Universal 3/8" Ratchet Wrench



Good for exhaust hanger clips and fastenings also sump bolts - Product Specification: Speed: 150 rpm - Max Torque: 50 ft lbs (68 Nm) - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 254 mm (10 ins) - Height: 38 mm (1.5 ins) - Nett Weight: 1.13 kgs (2.5 lbs) - Vibration Level: 8.5 m/sec² - Sound Pressure: 88.0 db(A) - Square Drive: 3/8 ins - Bolt Capacity: 3/8 ins (9.525 mm) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8005 | 3/8 | 71.00 |
| UT8015 | 1/2 | 71.00 |

Universal Composite 3/8" Pistol Grip Wrench



Lightweight pistol Wrench suitable for wheel removal on light vehicles - Product Specification: Speed: 9,200 rpm - Max Torque: 300 ft lbs (407 Nm) - Average Air Consumption: 3.2 cfm - Compressor FAD: 12 cfm - Length: 165 mm (6.5 ins) - Height: 160 mm (6.3 ins) - Nett Weight: 1.2 kgs (2.6 lbs) - Vibration Level: 5 m/sec² - Sound Pressure: 85.0 db(A) - Air Inlet: 1/4 ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8026 | 3/8 | 154.00 |

Universal 1/2" Pistol Wrench - Rubber Grip



Ideal for medium wheel work and most suspension/steering joints - Product Specification: Speed: 6,500 rpm - Max Torque: 310 ft lbs (420 Nm) - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 190 mm (7.5 ins) - Height: 190 mm (7.5 ins) - Nett Weight: 2.4 kgs (5.3 lbs) - Vibration Level: 2.5 m/sec² - Sound Pressure: 90.3 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8135RE | 1/2 | 125.00 |

Universal Composite Pistol Grip Impact Wrench



Ideal for heavy wheel work and most suspension/steering joints - Product Specification: Speed: 9,000 rpm - Max Torque: 580 ft lbs (786 Nm) - Average Air Consumption: 5.7 cfm - Compressor FAD: 12 cfm - Length: 195 mm (7.7 ins) - Height: 170 mm (6.7 ins) - Nett Weight: 2 kgs (4.4 lbs) - Vibration Level: 6.75 m/sec² - Sound Pressure: 85.0 db(A) - Air Inlet: 1/4 ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8126 | 1/2 | 171.00 |

Garage Equipment, Airtools & Handtools

Universal 19.2v 1/2" Cordless Impact Wrench



Torque control facility works well and is a major benefit to Tyre shops and mobile tyre truck - Product Specification: No Load Speed: 1,800 rpm - Impacts Per Minute: 2,600 - Max Torque: 400 ft lbs (542 Nm) - Length: 254 mm (10 ins) - Height: 269 mm (10.6 ins) - Nett Weight: 3.2 kgs (7 lbs) - Vibration Level: 5.89 m/sec2 - Volt DC: 19.2 volts - Charge Time: 60 mins

| Part No. | Size | Price £ |
|----------|------|------------|
| HP192ATC | 1/2 | 299.00 |

Universal 3/4" SQ Drive Impact Wrench



Good general duty tool suitable for many agricultural applications - Product Specification: Speed: 5,000 rpm - Max Torque: 850 ft lbs (1152 Nm) - Average Air Consumption: 8 cfm - Compressor FAD: 16 cfm - Nett Weight: 4.8 kgs (10.6 lbs) - Vibration Level: 5.8 m/sec2 - Sound Pressure: 85.7 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UTS315 | 3/4 | 265.00 |

Universal 3/8" Reversible Drill



Suitable for Drilling and Tapping all sheet metal and window frame applications - Product Specification: Chuck Size: 3/8 ins - Chuck Type: Chuck With Key - Speed: 1,800 rpm - Average Air Consumption: 4 cfm - Compressor FAD: 16 cfm - Length: 150 mm (5.9 ins) - Height: 125 mm (4.9 ins) - Nett Weight: 1.36 kgs (3 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 91.0 db(A) - Thread Size: 3/8' x 24mm UNF - Reversible: Yes - Air Inlet: 1/4 BSP ins - UT5825K Keyless Chuck

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5825 | 3/8 | 69.00 |
| UT5825K | 3/8 | 79.00 |

Universal Drill 1/2" Reversible (500 rpm) Keyless



Fitted with a keyless chuck and suitable for Drilling and Tapping all sheet metal and window frame applications - Product Specification: Chuck Size: 1/2 ins - Chuck Type: Keyless - Speed: 500 rpm - Average Air Consumption: 4 cfm - Compressor FAD: 16 cfm - Length: 206 mm (8.1 ins) - Height: 126 mm (5 ins) - Nett Weight: 1.5 kgs (3.3 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 91.0 db(A) - Thread Size: 3/8' x 24mm UNF - Reversible: Yes - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5880 | 1/2 | 147.00 |

Universal 3/8" Drill Straight Keyless



Ideal for Drilling in sheet metal / Aluminium fabrications where ergonomic or access for pistol drill is unsuitable - Product Specification: Chuck Size: 3/8 x 24 ins - Speed: 4,500 rpm - Average Air Consumption: 4 cfm - Compressor FAD: 16 cfm - Length: 220 mm (8.7 ins) - Height: 37 mm (1.5 ins) - Nett Weight: 0.9 kgs (2 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 89 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5741A | 3/8 | 88.00 |

Universal 1/4" Direct Drive Pistol Screwdriver



Most suitable for Woodworking applications - torque adjustment are regulated by air pressure - Product Specification: Speed: 1,800 rpm - Max Torque: 30 lbs ins (3.39 Nm) - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 178 mm (7 ins) - Height: 140 mm (5.5 ins) - Nett Weight: 1.36 kgs (3 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 91.0 db(A) - Square Drive: 1/4 HEX ins - Bolt Capacity: 3/16 ins (4.7625 mm) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5825S | 1/4 | 79.00 |

Universal Pistol External Adjust Clutch Screwdriver



Externally adjustable clutch gives optimum advantage with multi-size screwdriving operations - Product Specification: Speed: 1,800 rpm - Max Torque: 71 lbs ins (8.02 Nm) - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 190 mm (7.5 ins) - Height: 140 mm (5.5 ins) - Nett Weight: 1 kgs (2.2 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 84.3 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5964A | 1/4 | 150.00 |

Universal 7" Angle Sander



Ideal tool for light industrial metalwork fabrications - Product Specification: Speed: 4,500 rpm - Average Air Consumption: 8 cfm - Compressor FAD: 25 cfm - Length: 317 mm (12.5 ins) - Height: 47 mm (1.9 ins) - Nett Weight: 2.3 kgs (5.1 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 95.7 db(A) - Pad Size: 7 ins (178 mm) - Thread Size: 5/8" UNC - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8751 | 7" | 198.00 |

Universal Angle Head 90° Die Grinder



Multiple applications such as grinding and polishing through the use of Carbide Burrs - Mounted Stones - Bristle discs flap wheels and Scotchbrite Disc's - Product Specification: Speed: 22,000 rpm - Standard Collet Size: 6 mm - Collet Size: 6 - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 140 mm (5.5 ins) - Height: 75 mm (3 ins) - Nett Weight: 0.5 kgs (1.1 lbs) - Vibration Level: <2.5 m/sec2 - Sound Pressure: 86 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------------------------|------------|
| UT5715 | Angle Head Die Grinder | 102.00 |

Universal Extended Die Grinder



Perfect tools for removal of light flashing on Forgings - cleaning up and smoothing welds - Product Specification: Speed: 25,000 rpm - Horsepower: 0.5 HP (373 watts) - Collet Size: 6mm - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 255 mm (10 ins) - Height: 43 mm (1.7 ins) - Nett Weight: - 0.66 kgs (1.5 lbs) - Vibration Level: 4.53 m/sec2 - Sound Pressure: 91.0 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|----------------------|------------|
| UT5735 | Extended Die Grinder | 116.00 |

Universal Rear Exhaust Die Grinder c/w Cover



Multiple applications of light grinding through the use of Carbide Burrs - and Mounted Stones - Product Specification: Speed: 25,000 rpm - Standard Collet Size: 6 mm - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 156 mm (6.1 ins) - Height: 45 mm (1.8 ins) - Width: 0.62 mm - Vibration Level: <2.5 m/sec2 - Sound Pressure: 86 db(A) - Internal Thread: 1 3/8" x 20 unf - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|-------------|------------|
| UT5720A | Die Grinder | 66.00 |

Universal 4" Angle Grinder



Good all round grinder suitable for Medium duty grinding - wire brush and flap disc applications - Product Specification: Speed: 12,000 rpm - Average Air Consumption: 10 cfm - Compressor FAD: 30 cfm - Length: 220 mm (8.7 ins) - Height: 50 mm (2 ins) - Angle Head Height: 85 mm - Nett Weight: 1.76 kgs (3.9 lbs) - Vibration Level: 5.1 m/sec2 - Sound Pressure: 82.9 db(A) - Thread Size: M10 x 1.25 - Wheel Capacity: 4 ins (102 mm) - 4.5 ins (114 mm) - 5 ins (127 mm) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|--------|------------|
| UT8750 | 4" | 194.00 |
| UT8750A | 4 1/2" | 194.00 |
| UT8750B | 5" | 194.00 |

Universal Hammer Kit With 5 Chisels



Good general duty hammer Kit (including 5 mixed chisels + extra spring) for multiple applications including Exhaust work - Multiple Bodyshop work - Scraping and chiselling applications - Product Specification: Shank Size: 0.401 ins - Blows per minute: 3,500 - Average Air Consumption: 4 cfm - Compressor FAD: 12 cfm - Length: 200 mm (7.9 ins) - Height: 145 mm (5.7 ins) - Nett Weight: 1.95 kgs (4.3 lbs) - Vibration Level: 2.35 m/sec² - Sound Pressure: 94.26 db(A) - Piston Bore: 19 mm - Stroke: 67 mm (2.6 ins) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|------------|--------------------------|------------|
| UT8612LVBK | Low Vibration Hammer Kit | 120.00 |

Universal High Speed Reciprocal Saw



General duty tool most suitable for cutting sheet metal body panels and light plywood applications - Product Specification: Strokes per minute: 10,000 - Average Air Consumption: 4 cfm - Compressor FAD: 16 cfm - Length: 199 mm (7.8 ins) - Height: 40 mm (1.6 ins) - Nett Weight: 0.6 kgs (1.3 lbs) - Vibration Level: 24.1 m/sec² - Sound Pressure: 79 db(A) - Capacity in Aluminium: 2 mm - Capacity in Steel: 1.6 mm - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|---------|------------|
| UT5920 | Air Saw | 102.00 |

Universal DA Orbit Sander Non Vacuum



General duty tool with non dust extraction - Pad can be locked to provide standard rotary or orbital action - suitable for medium finish - Product Specification: Speed: 10,000 rpm - Average Air Consumption: 6 cfm - Compressor FAD: 20 cfm - Length: 285 mm (11.2 ins) - Height: 130 mm (5.1 ins) - Nett Weight: 1.8 kgs (4 lbs) - Vibration Level: <2.5 m/sec² - Sound Pressure: 94.0 db(A) - Pad Size: 6 ins (152 mm) - Orbit: 5 mm - Thread Size: 5/16 - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|-------------|------------|
| UT8788 | D A Grinder | 66.00 |

Universal 6" D.A Palm Sander - Non Vacuum 5mm Orbit



5mm Orbital Sander perfect for medium/fine finish sanding - non dust extraction - Product Specification: Speed: 10,000 rpm - Average Air Consumption: 5 cfm - Compressor FAD: 20 cfm - Length: 150 mm (5.9 ins) - Height: 98 mm (3.9 ins) - Nett Weight: 0.9 kgs (2 lbs) - Vibration Level: <2.5 m/sec² - Sound Pressure: 78 db(A) - Pad Size: 6 ins (152 mm) - Orbit: 5 mm - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8700 | 6" | 158.00 |

Universal 6" D.A Palm Sander With Dust Bag



5mm Orbital Sander perfect for medium/fine finish sanding - fitted with self dust extraction facility - Product Specification: Speed: 10,000 rpm - Average Air Consumption: 5 cfm - Compressor FAD: 20 cfm - Length: 150 mm (5.9 ins) - Height: 98 mm (3.9 ins) - Nett Weight: 0.9 kgs (2 lbs) - Vibration Level: <2.5 m/sec² - Sound Pressure: 78 db(A) - Pad Size: 6 ins (152 mm) - Orbit: 5 mm - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|---------------------------------------|------------|
| UT8701 | Self Generating VAC-6" Orbital Sander | 180.00 |

Universal 6" D.A Palm Sander - Central Vac 5mm Orbit



5mm Orbital Sander perfect for medium/fine finish sanding - fitted with dust extraction facility - Product Specification: Speed: 10,000 rpm - Average Air Consumption: 5 cfm - Compressor FAD: 20 cfm - Length: 150 mm (5.9 ins) - Height: 98 mm (3.9 ins) - Nett Weight: 0.9 kgs (2 lbs) - Vibration Level: <2.5 m/sec² - Sound Pressure: 78 db(A) - Pad Size: 6 ins (152 mm) - Orbit: 5 mm - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT8702 | 6" | 158.00 |

Universal Belt Sander 10mm x 328mm



Light duty 10mm belt sander - suitable for multiple application around the bodyshops and woodworking industries - Product Specification: Belt Size: 330 X 10 mm - Speed: 16,000 rpm - Average Air Consumption: 6 cfm - Compressor FAD: 20 cfm - Length: 260 mm (10.2 ins) - Height: 75 mm (3 ins) - Nett Weight: - 0.78 kgs (1.7 lbs) - Vibration Level: <2.5 m/sec² - Sound Pressure: 85.0 db(A) - Air Inlet: 1/4 BSP ins - Belts Included: 1 x 80 - 100 - 120 Grit

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5764 | 10mm | 116.00 |

Universal Belt Sander 20mm x 520mm



Product Specification: Belt Size: 520 X 20 mm - Speed: 16,000 rpm - Average Air Consumption: 6 cfm - Length: 340 mm - Height: 95 mm - Nett Weight: 1.15kgs - Vibration Level: <2.5 m/sec² - Sound Pressure: 85.0 db(A) - Air Inlet: 1/4 BSP ins

| Part No. | Size | Price £ |
|----------|------|------------|
| UT5765 | 20mm | 243.00 |

Universal 3/16" Capacity Pop Rivet Gun



Product Specification: Traction Power: 1,100 lbs - Av Air Con: 2 cfm - Weight: 1.5kg - Nosepieces: 3/32" (2.4mm) - 1/8" (3.2mm) - 5/32" (4.0mm) - 3/16" (4.8mm) - Vibration Level: <2.5 m/sec² - Sound Pressure: 77 db(a) - Length: 270 mm - Width: 98 mm - Rivet Capacity 3/32"-3/16" - Air Inlet: 1/4 bsp - With Rubber base plate and swivel joint (connector)

| Part No. | Size | Price £ |
|----------|-------|------------|
| UT40PPA | 3/16" | 126.00 |



See From Page 24/11 For Our
Full Range Of PCL Air Tools &
Accessories




Universal Sander Belts - Pack Of 10



Universal Sander Belts - Pack Of 10

| Part No. | Width | Grit | Price £ |
|------------|-------|------|------------|
| UT8764-40 | 10mm | 40 | 11.10 |
| UT8764-60 | 10mm | 60 | 11.10 |
| UT8764-100 | 10mm | 100 | 11.10 |
| UT8764-150 | 10mm | 150 | 11.10 |
| UT8765-40 | 20mm | 40 | 17.40 |
| UT8765-60 | 20mm | 60 | 17.40 |
| UT8765-100 | 20mm | 100 | 17.40 |
| UT8765-150 | 20mm | 150 | 17.40 |

Universal 6" Backing Pads For Sanders



Universal 6" Backing Pads For Sanders

| Part No. | Description | Price £ |
|----------|---------------------------------|------------|
| H0018V | 6" VELCRO DUAL ACTION PAD | 9.30 |
| H0102 | 6" VELCRO PAD FOR UT8700 | 28.20 |
| H0103 | 6" VELCRO PAD FOR UT8701 & 8702 | 28.20 |

Universal Drill Chucks And Keys



Universal Drill Chucks And Keys

| Part No. | Description | Price £ |
|----------|--------------------|------------|
| H0019 | 3/8" CHUCK AND KEY | 8.40 |
| H0019K | 3/8" KEYLESS CHUCK | 18.60 |
| H0020 | 1/2" CHUCK AND KEY | 22.50 |
| H0020K | 1/2" KEYLESS CHUCK | 37.20 |

Universal Impact Socket Sets



Universal Impact Socket Sets

| Part No. | Description | Sizes | Price £ |
|----------|-----------------------------|--|------------|
| H0072 | 3/8" mm impact sockets | 9 - 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19 | 28.80 |
| H0073 | 3/8" mm long impact sockets | 8 - 10 - 11 - 13 - 14 - 16 - 17 - 19 | 34.80 |
| H0082 | 1/2" mm impact sockets | 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19 - 21 - 22 - 24 | 34.80 |
| H0082-MM | long impact sockets | 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19 - 21 - 22 - 24 | 54.00 |
| H0086-1 | 3/4" mm impact sockets | 24 - 27 - 29 - 30 - 32 - 33 - 36 - 38 | 116.40 |

Universal Impact Extension Bars



Universal Impact Extension Bars

| Part No. | Description | Price £ |
|----------|-----------------|------------|
| EX383 | 3/8" X 3" long | 13.20 |
| EX386 | 3/8" X 6" long | 13.20 |
| EX123 | 1/2" X 3" long | 13.80 |
| EX126 | 1/2" X 6" long | 13.80 |
| EX1210 | 1/2" X 10" long | 18.30 |
| EX346 | 3/4" X 6" long | 35.10 |
| EX3410 | 3/4" X 10" long | 36.00 |

Universal Socket Adaptors



Universal Socket Adaptors

| Part No. | Description | Price £ |
|----------|--------------------------|------------|
| SA38F12M | 3/8" female to 1/2" male | 17.10 |
| SA12F38M | 1/2" female to 3/8" male | 17.10 |
| SA12F34M | 1/2" female to 3/4" male | 17.70 |
| SA34F12M | 3/4" female to 1/2" male | 18.90 |

Universal Joint



Universal Joint

| Part No. | Description | Price £ |
|----------|----------------------|------------|
| UJ38 | 3/8" UNIVERSAL JOINT | 31.50 |
| UJ12 | 1/2" UNIVERSAL JOINT | 35.40 |
| UJ34 | 3/4" UNIVERSAL JOINT | 75.00 |


Universal Tool Oil



Universal Tool Oil

| Part No. | Description | Price £ |
|----------|----------------------------|------------|
| H0076 | 4 fluid oz Marvel tool oil | 2.00 |
| H0077 | 1 us Quart Marvel tool oil | 8.25 |

Universal Screwdriver Accessories



Universal Screwdriver Accessories

| Part No. | Description | Price £ |
|----------|--------------------------------------|------------|
| H1001 | No 1 Pozzi power bit 1 15/16" long | 3.30 |
| H1002 | No 2 Pozzi power bit 1 15/16" long | 3.30 |
| H1003 | No 3 Pozzi power bit 1 15/16" long | 3.30 |
| H1001P | No1 Phillips power bit 1 15/16" long | 3.30 |
| H1002P | No2 Phillips power bit 1 15/16" long | 3.30 |
| H1003P | No3 Phillips power bit 1 15/16" long | 3.30 |
| H1010 | Insert bit holder 2 3/8" long | 11.10 |
| H1010M | Magnetic bit holder assembly 3" long | 23.70 |
| H1011 | No1 Pozzi insert bit 1" long | 2.10 |
| H1012 | No 2 Pozzi insert bit 1" long | 2.10 |
| H1013 | No 3 Pozzi insert bit 1" long | 2.10 |
| H1015 | Socket adaptor 1/4" Hex to 3/8" sq m | 17.10 |
| H1016 | Socket adaptor 1/4" Hex to 1/4" sq m | 16.50 |
| H1018 | 1/4" Hex M to 5/16" F Hex adaptor | 50.40 |

Redashe

Redashe Toptul Hand Tools

TOPTUL®
THE WORLD OF PROFESSIONAL TOOLS

Redashe® Toptul® 18pc 1/2" drive Metric Socket Set



1/2" Drive Metric Socket Set: 18pcs contained in a Quality Metal Box with insert tray. Set contents: 15" Swivel handle - universal joint - quick release ratchet with comfort handle - 3" extension - 5" extension - 12" extension. Sockets 10, 12, 14, 17, 19, 21, 22, 24, 27, 30, 32

| Part No. | Price £ |
|----------|------------|
| RCAD1802 | 100.10 |

Redashe® Toptul® 25 pc 3/8" drive Metric Socket Set



3/8" Drive Metric Socket Set: Set contents: 25pcs (All 3/8" Drive) Contained in an Quality Metal Box with insert tray. Contents quick release ratchet with comfort handle - sliding T Bar 5/8" and 13/16" magnetic spark plug sockets - 3" extension - 6" extension - sockets ranging from 6mm - 22mm - + 24mm - universal joint

| Part No. | Price £ |
|----------|------------|
| RAAD2501 | 62.70 |

Redashe® Toptul® 10 pc 1/2" drive Metric Hex Bit Socket Set



1/2" Drive Metric Hex Bit Socket Set - superb quality - extremely robust - mirror finish - supplied in a quality metal box: 10pcs: 1/2" x 4 - 5 - 6 - 7 - 8 - 10 - 12 - 14 - 17 - 19

| Part No. | Price £ |
|----------|------------|
| RAAD1008 | 35.20 |

Redashe® Toptul® 13 pc 3/8" Drive Standard Metric Socket Set



3/8" Drive Standard Metric Sockets: High quality - robust - exceeds international ASNI and DIN standards - maxi drive - flat to flat drive giving more turning power - thin wall design - allows easier access into restricted areas - constructed in CRV - strong - durable - superb mirror finish - easy clean - easily portable - supplied on socket rail with clips on carry handle - sizes: 7mm - 17mm + 19mm - 21mm

| Part No. | Price £ |
|----------|------------|
| RAAQ1302 | 14.30 |

Redashe® Toptul® 13 pc 1/4" Drive Deep Metric Socket Set



13pcs 1/4" Drive Deep Metric Sockets: high quality - robust - exceeds international ASNI and DIN standards - maxi drive - flat to flat drive giving more turning power - thin wall design - allows easier access into restricted areas - constructed in CRV - strong - durable - superb mirror finish - easy clean - easily portable - supplied on socket rail with clip on carry handle - sizes: 4 - 4.5 - 5 - 5.5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13 - 14mm

| Part No. | Price £ |
|----------|------------|
| RAAQ1304 | 19.80 |

Redashe® Toptul® 13 pc 3/8" Drive Deep Metric Socket Set



13pcs 3/8" Drive Deep Metric Socket: high quality - robust - exceeds international ASNI and DIN standards - maxi drive - flat to flat drive giving more turning power - thin wall design allows easier access into restricted areas - constructed in CRV - strong - durable - superb mirror finish - easy clean - supplied on socket rail with clips on carry handle. Sizes: 7mm - 17mm + 19mm - 21mm

| Part No. | Price £ |
|----------|------------|
| RAAQ1305 | 27.50 |

Redashe® Toptul® 11 pc 1/2" Drive Deep Metric Socket Set



15° 1/2" Drive Deep Metric Sockets: high quality - robust - exceeds international ASNI and DIN standards - maxi drive - flat to flat drive giving more turning power - thin wall design allows easier access into restricted areas - constructed in CRV - strong - durable - superb mirror finish - easy clean - supplied on socket rail with clips on carry handle 11pcs. Sizes: 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 19 - 21 - 22mm

| Part No. | Price £ |
|----------|------------|
| RAAQ1107 | 13.90 |

Redashe® Toptul® 8 pc 3/8" Drive Star Bit Set



3/8" Drive Star Bit Set: Constructed in CRV - strong - durable - superb mirror finish - easy clean - supplied on socket rail with clips - 8pcs contents: T15 - T20 - T25 - T27 - T30 - T40 - T45 - T50

| Part No. | Price £ |
|----------|------------|
| RAAG0803 | 13.20 |

Redashe® Toptul® 8pc: 3/8" Drive Star Socket



High quality - robust - exceeds international ASNI and DIN standards - constructed in CRV - strong - durable - superb mirror finish - easy clean - easily portable - supplied on socket rail with clips. 8pcs contents: E8 - E10 - E11 - E12 - E14 - E16 - E18 - E20

| Part No. | Price £ |
|----------|------------|
| RAAG0801 | 11.00 |

Redashe® Toptul® 7pc: 3/8" Drive Hex Bit Set



3/8" Drive Metric Hex Socket: Constructed in CRV - strong - durable - superb satin finish - easy clean - supplied on socket rail with clips. 7pcs contents: 3 - 4 - 5 - 6 - 7 - 8 - 10mm

| Part No. | Price £ |
|----------|------------|
| RAAG0701 | 11.52 |

Redashe® Toptul® 10 - Piece Stubby Metric Combination Wrench Set



Stubby Metric Combination Wrench Set: Constructed in Chrome Vanadium Steel - strong and durable - high quality - robust - exceeds international ASNI and DIN standards - superb mirror finish - easy clean - professional quality for convenient operation in confined spaces. 10pc sizes: 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19mm

| Part No. | Price £ |
|----------|------------|
| RAAF1001 | 33.00 |

Redashe® Toptul® 12 - Piece Metric Combination Wrench Set



Metric Combination Wrench Set: Constructed in Chrome Vanadium Steel - strong and durable - high quality - robust - exceeds international ASNI and DIN standards - superb mirror finish - easy clean - professional quality. Larger sizes available. up to 36mm . Sizes: 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13 - 14 - 15 - 17 - 19mm

| Part No. | Price £ |
|----------|------------|
| RAAE1210 | 42.90 |

Redashe® Toptul® 10 - Piece Extra long Metric Combination Wrench Set



Extra long Combination Wrench Set: Constructed in Chrome Vanadium Steel – strong and durable - high quality - robust - exceeds international ASNI and DIN standards - superb mirror finish - easy clean - professional quality. Perfect when extra torque is required. 10pc sizes: 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19mm

| Part No. | Price £ |
|----------|------------|
| RAAF1007 | 68.20 |

Redashe® Toptul® 8 - Piece Dynamic Drive Metric Combi Wrench Set



15° offset Dynamic Drive Combination Wrench Set: Constructed in Chrome Vanadium Steel – strong and durable - high quality - robust - exceeds international ASNI and DIN standards - superb mirror finish - easy clean - professional quality. Designed for operating in a 30° restricted space. Supplied in a quality canvas kit bag. 8pc sizes: 10 - 11 - 12 - 13 - 14 - 15 - 17 - 19mm.

| Part No. | Price £ |
|----------|------------|
| RAAA0805 | 41.80 |

Redashe® Toptul® 7 - Piece Metric Reversible Gear Wrench Set



72 Teeth gear construction with only a 5° increment between clicks for optimum fastening efficiency. Constructed in Chrome Vanadium Steel – strong and durable - high quality - robust - exceeds international ASNI and DIN standards - super smooth satin finish. Supplied in a handy storage rack. 7pc sizes: 10 - 11 - 13 - 14 - 16 - 17 - and 19mm.

| Part No. | Price £ |
|----------|------------|
| RAAM0708 | 118.80 |

Redashe® Toptul® 23 - Piece Star Wrench Sockets & Key Wrench Set



Star Wrench Sockets & Key Wrench Set: 23pcs contained in a plastic insert tray. Set contents: 4 pieces ¼" Drive star sockets - E4 - E5 - E6 - E8 - 6 pieces ½" Drive star sockets E10 - E12 - E14 - E16 - E18 - E20 - 9 pieces short type star key wrench set T10 - T15 - T20 - T25 - T27 - T30 - T40 - T45 - T50 - 4 pieces star wrench - Double Ended E6 x E8 - E10 x E12 - E14 x E18 - E20 x E24

| Part No. | Price £ |
|----------|------------|
| RAAT2301 | 55.00 |

Redashe® Toptul® Individual large Standard combination wrenches 22 - 36mm



Individual large Standard combination wrenches 22 - 36mm

| Part No. | Size (MM) | Price £ |
|----------|-----------|------------|
| RAAB2222 | 22 | 7.70 |
| RAAB2424 | 24 | 9.90 |
| RAAB2727 | 27 | 12.10 |
| RAAB3030 | 30 | 15.40 |
| RAAB3232 | 32 | 17.60 |
| RAAB3636 | 36 | 29.70 |

Redashe® Toptul® 1/2" Drive Quick Release Ratchet



1/2" Drive Quick Release Ratchet: Constructed in CRV - strong - durable - ergonomic handle - comfortable to use - 36 gear design - 10° movement between teeth - superb mirror finish - easy clean - quick release mechanism - easy to remove and replace sockets - reverse lever - easy single hand operation to change direction

| Part No. | Price £ |
|----------|------------|
| RHAG1626 | 18.70 |

Redashe® Toptul® 3/8" Drive Quick Release Ratchet



3/8" Drive Quick Release Ratchet: Constructed in CRV - strong - durable - ergonomic handle - comfortable to use - 36 gear design - 10° movement between teeth - superb mirror finish - easy clean - quick release mechanism - easy to remove and replace sockets - reverse lever - easy single hand operation to change direction

| Part No. | Price £ |
|-----------------|--------------|
| RHAG1218 | 14.30 |

Redashe® Toptul® 1/4" Drive Quick Release Ratchet



1/4" Drive Quick Release Ratchet: Constructed in CRV - strong - durable - ergonomic handle - comfortable to use - 36 gear design - 10° movement between teeth - superb mirror finish - easy clean - quick release mechanism - easy to remove and replace sockets - reverse lever - easy single hand operation to change direction

| Part No. | Price £ |
|-----------------|--------------|
| RHAG0813 | 11.00 |

Redashe® Toptul® 1/2" Drive Flex Head Quick Release Ratchet



1/2" Drive Flexible Quick Release Ratchet: Constructed in CRV - strong - durable - ergonomic handle - comfortable to use - 36 gear design - 10° movement between teeth - superb mirror finish - easy clean

| Part No. | Price £ |
|-----------------|--------------|
| RHLI1628 | 28.60 |

Redashe® Toptul® 3/8" Drive Flex Head Quick Release Ratchet



3/8" Drive Flexible Quick Release Ratchet: Constructed in CRV - strong - durable - ergonomic handle - comfortable to use - 36 gear design - 10° movement between teeth - superb mirror finish - easy clean

| Part No. | Price £ |
|-----------------|--------------|
| RHLI1227 | 26.40 |

Redashe® Toptul® 3/8" Stubby Swivel Headed Ratchet with Bit Drive



Stubby Swivel Head Ratchet with Bit Drive: Constructed in CRV - strong - durable - soft grip handle - 3/8" drive + 1/4" female bit driver - swivel head can be used through a full 180° for difficult access jobs - fine tooth - 72 teeth - allows access into tight spaces - versatile can also be used "in-line" as a nut spinner. or ratchet screwdriver

| Part No. | Price £ |
|-----------------|--------------|
| RJOM1216 | 33.00 |

Redashe® Toptul® 3/8" Stubby Swivel Headed Ratchet with Bit Drive



Stubby Swivel Head Ratchet with Dual Drives: Constructed in CRV - strong - durable - soft grip handle - comfortable to use - dual drives - convenient 1/4" & 3/8" drives - swivel head can be used through a full 180° for difficult access jobs - fine tooth - 72 teeth - allows access into tight spaces - versatile - can also be used "in-line" as a nut spinner.

| Part No. | Price £ |
|-----------------|--------------|
| RJMM1216 | 30.80 |

Redashe® Toptul® 1/2" Drive Breaker Bar



24" 1/2" Drive Breaker Bar: Constructed in CRV - strong - durable - ergonomic design handle - essential for unfastening those extra tight nuts & bolts. Superb quality

| Part No. | Price £ |
|----------|------------|
| RCFB1624 | 27.50 |

Redashe® Toptul® LED Adaptor



LED Adaptor: LED light passes directly through the socket - supplied complete with 3/8" (f) x 1/2" (m) spinner - supplied complete with spare battery set.

| Part No. | Drive | Price £ |
|----------|-------|------------|
| RBAR0203 | 3/8 | 13.20 |
| RBAR0205 | 1/2 | 13.20 |

Redashe® Toptul® Magnetic Two Way Adaptor



Magnetic adaptor which can be used in conjunction with a 19 mm wrench - 1/4" or 3/8" drive sockets

| Part No. | Size (MM) | Price £ |
|----------|------------------|------------|
| RAKA1923 | 1/4 x 3/8 x 19mm | 4.40 |
| RANA1619 | 1/2 x 19mm | 4.40 |
| RANA1213 | 3/8 x 13mm | 3.80 |
| RANA0810 | 1/4 x 10mm | 2.89 |

Redashe® Toptul® 9 Piece - Ball Point Hex Key Wrench Set



Metric Long Ball Point Hex Key Wrench Set: Ball end allows the wrench to be used at an angle allowing greater access. Supplied on a convenient belt clip. DIN/ASNI standard - SNCM + V Alloy steel - durable - satin chrome finish 9pcs contents: 1.5 - 2 - 2.5 - 3 - 4 - 5 - 6 - 8 - 10mm

| Part No. | Price £ |
|----------|------------|
| RAAL0916 | 15.40 |

Redashe® Toptul® Dead Blow Hammer



Shot filled head helps to prevent rebound when surface is struck - ribbed handle helps to prevent slippage.

| Part No. | Price £ |
|----------|------------|
| RAAB1038 | 15.40 |

Redashe® Toptul® 16 oz Ball Pein Hammer



Superb quality - well balanced with hickory handle.

| Part No. | Price £ |
|----------|------------|
| RAAC1035 | 15.40 |

Redashe® Toptul® 11" C Clamp



Wide-opening jaws provide greater versatility in clamping a variety of shapes. Adjust the pressure by turning the screw to fit job. Constructed of high-grade heat-treated alloy steel for maximum toughness and durability. Guarded release trigger quickly unlocks and protects from accidental release.

| Part No. | Price £ |
|----------|------------|
| RAAU1A11 | 17.60 |

Redashe® Toptul® 9" Welding Clamp



U-shaped jaws provide enhanced visibility and more working space. Holds work in proper alignment for use in welding applications or for holding awkward shapes in place. Turn screw to adjust pressure and fit work. Stays adjusted for repetitive use.

| Part No. | Price £ |
|----------|------------|
| RAAT1A09 | 16.50 |

Redashe® Toptul® 8" Sheet Metal Clamp



Makes bending - forming - and crimping jobs easier Turn screw to adjust pressure and fit work. Stays adjusted for repetitive use. Constructed of high-grade heat-treated alloy steel for maximum toughness and durability. Guarded release trigger quickly unlocks and protects from accidental release.

| Part No. | Price £ |
|----------|------------|
| RAAV1A08 | 14.30 |

Redashe® Toptul® Door Upholstery Trim Pad Remover



Non-slip handle made from PP + TPR resins.

| Part No. | Price £ |
|----------|------------|
| RAAE0812 | 7.70 |

Redashe® Toptul® 3pcs Stainless Steel Bolstered Scraper Set



Contents: - Size 50mm T: 1.85mm L230mm - Size 32mm T: 1.85mm L230mm
- Size 32mm T: 1.85mm L230mm

| Part No. | Price £ |
|----------|------------|
| RGAT0302 | 27.50 |

Redashe® Toptul® Magnetic Pick Up Tool Flexible Handle



Flexible shaft bends and holds shape - ideal for retrieving dropped nuts - bolts - etc from hard to reach angles and around obstructions.

| Part No. | Price £ |
|----------|------------|
| RJAD0512 | 6.60 |

Redashe® Toptul® Miniature Hook and Pick Set



Each hook pick & Scribe is made of Stainless Steel. Soft Grip handle providing comfort and control while resisting most workshop solvent. Used for installing and removing O-rings - seals and washers - making holes in leather and fabric - scraping difficult areas - aligning and scribing. - Contents: - Mini hook - mini awl - mini bent tip 90° - Mini bent tip 45°.

| Part No. | Price £ |
|----------|------------|
| RAAR0401 | 12.10 |

Redashe® Toptul® 3 Piece Assorted Pliers Set



Multi-purpose cutting and gripping tools. Combination pliers 7" (L) – Chrome Vanadium Steel - Heavy duty Diagonal Cutting Pliers 7" (L) - Long Nose Pliers 8" (L) precision - hardened pliers head - high frequency hardened cutting edges - comfort non-slip handles - hot riveted ensures smooth action with no handle wobble.

| Part No. | Price £ |
|----------|------------|
| RAAT0302 | 47.30 |

Redashe® Toptul® 4 Piece Circlip Pliers Set



Chrome Vanadium Steel - spring assisted opening for internal or external - circlip - anti-slip - turned tips - comfort non-slip handles. Contents: straight retaining ring pliers 7" (internal) 90 retaining ring pliers 7" (internal) comfort non-slip handles.

| Part No. | Price £ |
|----------|------------|
| RAAT0404 | 46.20 |

Redashe® Toptul® 3 Piece Adjustable Wrench & Pliers Set



10" 25.5cm curved jaw locking pliers with wire cutter - 10" 25.5cm groove joint water pump pliers - 10" 25.5cm opening 33.3cm adjustable wrench

| Part No. | Price £ |
|----------|------------|
| RBAT0303 | 58.30 |

Redashe® Toptul® 4 piece Assorted Plier Set



Chrome molybdenum steel - hot riveted pivot joints ensures smooth action and no handle wobble - comfort grip handles - bevelled cutting edge - precision cutting - Contents: • Combination pliers 7" • Heavy duty diagonal cutting pliers 7" • Long nose pliers 8" • Bent nose pliers 8"

| Part No. | Price £ |
|----------|------------|
| RAAT0402 | 57.56 |

Redashe® Toptul® Go Thru Slotted & Philips Screwdriver Set



Specially hardened & tempered SNCM+V Steel round blade - hex shoulder for use with spanners (extra leverage) - high performance hardened magnetic tip - non-slip handle made from PP + TPR resins. Contents: Phillips PH1 x 75 - PH2 x 100 Slotted 5.5 x 100 - 6.5 x 150 - 8 x 175 - 10 x 200

| Part No. | Price £ |
|----------|------------|
| RAAT0601 | 38.50 |

Redashe® Toptul® 8 Piece Non-Slip Screwdriver Set



Specially hardened and tempered - SNCM+V steel blade - high performance black hardened magnetic tip - ergonomically designed non-slip handle.
Contents: Phillips PH1 x 80 - PH2 x 100 - PH3 x 150 - PH2 x 25 Slotted 4 x 100 - 5.5 x 100 - 6.5 x 150.

| Part No. | Price £ |
|----------|------------|
| RAAT0805 | 28.60 |

Redashe® Toptul® 31pcs Screwdriver Bit Set



Contents: Phillips PH0 - PH1 x 2pc - PH3 - Pozidrive PZ0 - PZ1 x 2 - PZ2 x 2pc - PZ3 Slotted 4 x 0.5 - 5.5 x 1 - 6.5 x 1.2mm - Star Drive T6 - T7 - T8 - T9 - T10 - T15 - T20 - T25 - T27 - T30 - T40 - 1/4" male x 1/4" female Magnetic Bit Holder

| Part No. | Price £ |
|----------|------------|
| RAAW1301 | 14.30 |



Ingersoll Rand Tools



Ingersoll-Rand® Cordless Drill Kit



Cordless Drill Kit with charger and 2 Lithium-Ion batteries - Features: Composite housing for strength and resistance to chemical attack - Twist lock battery interface (Patent pending) - One charger suits all tools - Increased power with smaller batteries for best-in-class power-to-weight - 1 hour fast charge - Renew feature refreshes battery and increases cycle life up to 4 times - Charge gauges on battery indicates how much charge is left at any time

| Part No. | Voltage | Chuck/Drive Size | Max Torque | Weight With Battery | Max Free Speed | Price £ |
|----------|---------|------------------|------------|---------------------|----------------|------------|
| D650-L | 19.2 v | 13mm chuck | 73 nm | 2.10 kg | 1300 rpm | 546.00 |

Ingersoll-Rand® Cordless Impact Wrench Kit



Cordless Impact Wrench Kit with charger and 2 Lithium-Ion batteries - Features: Composite housing for strength and resistance to chemical attack - Twist lock battery interface (Patent pending) - One charger suits all tools - Increased power with smaller batteries for best-in-class power-to-weight - 1 hour fast charge - Renew feature refreshes battery and increases cycle life up to 4 times - Charge gauges on battery indicates how much charge is left at any time

| Part No. | Voltage | Chuck/Drive Size | Max Torque | Weight With Battery | Max Free Speed | Price £ |
|----------|---------|-------------------|------------|---------------------|----------------|------------|
| W360-2L | 19.2 v | 1/2" square drive | 488 nm | 3.85kg | 1650 rpm | 815.00 |



Ultrasound Leak Detector



PVL® Soundsonic Ultrasound Leak Detector



The Soundsonic Leak detection kit is ideal for finding compressed air and refrigerant leaks, the Soundsonic kit comes complete with a FREE ultrasonic sound Transmitter for checking enclosure seals etc - Please call the Sales office for the full technical specification of this product and how it can save you and your customers money.

| Part No. | Price £ |
|----------|------------|
| PBL30670 | 563.00 |

Redashe

Redashe Coolite

Redashe

Redashe® Coolite® 230v AC Input



Safe and easy to use – the LED elements generate very little heat and therefore you do not have the danger of touching an extremely hot surface.
- Features: 10x more efficient than incandescent bulbs - Shatterproof - water and oil resistant - 30 extremely long life LEDs – (J000L6-60 has 60 LEDs) - On/off switch - 1 year warranty - ROHS compliant

| Part No. | Description | Price £ |
|-----------|------------------|------------|
| J000L6-30 | Coolite® 30 LEDs | 57.68 |
| J000L6-60 | Coolite® 60 LEDs | 67.00 |

Redashe® Coolite® J1500 Mains Rechargeable



Safe and easy to use – the LED elements generate very little heat and therefore you do not have the danger of touching an extremely hot surface.
- Features: Powered by 30 high intensity LED bulb - High visibility colours - Rechargeable from either mains or 12v in-car supply - Ten times the efficiency of incandescent bulbs - Shock resistant & Oil resistant - Battery: Li-polymer 3.7v 1800MAH - Active life 5 hours - Full recharge time 4.5 hours - Charger input: DC11-28v - Low self discharge & Blister packed.

| Part No. | Description | Price £ |
|-------------|------------------------------|------------|
| J1500YELLOW | Coolite® Rechargeable Yellow | 42.86 |
| J1500ORANGE | Coolite® Rechargeable Orange | 42.86 |
| J1500GREEN | Coolite® Rechargeable Green | 42.86 |

Redashe® Coolite® J 000L 1100 Under Bonnet Lamp



Safe and easy to use – the LED elements generate very little heat and therefore you do not have the danger of touching an extremely hot surface - Features: Shatterproof - water and oil resistant - Powered by 120 high intensity LED bulbs - Ten times the efficiency of incandescent bulbs - Extremely long life bulb - On/off switch - ROHS compliant - 8 metre cable

| Part No. | Description | Price £ |
|-----------|----------------------------|------------|
| J000L1100 | Coolite® Under Bonnet Lamp | 121.00 |

Redashe® Coolite® J 000L8-30 Rechargeable



Safe and easy to use – the LED elements generate very little heat and therefore you do not have the danger of touching an extremely hot surface.
- Features: 10x more efficient than incandescent bulbs - Shatterproof - water and oil resistant - 36 extremely long life LED's - Two function On/off switch – Lamp or torch - 1 year warranty - In-car charging - Magnetic base - Combined Hook & Stand - 6 LEDs in the top for use as a flashlight - ROHS compliant - Battery 7.2v 1800 MAH-NIMH.

| Part No. | Description | Price £ |
|-----------|-----------------------|------------|
| J000L8-30 | Coolite® Rechargeable | 69.00 |

Confused?

then try our new

Conversion Tables

in the rear of the catalogue

