

Redashe

Redashe Lubrication

Redashe

Redashe® Lubeworks® Pistol Grip Grease gun



Features: Single hand operation grease gun - Supplied with flexible extension & 4-jaw coupler - Accepts standard 400g cartridges

Part No.	Description	Price £
J1786501	Pistol Grip Grease gun	23.00

Redashe® Lubeworks® Heavy Duty Lever Grease gun



Features: Rigid extension with 4-jaw coupler - Delivers up to 7.000psi/480bar of pressure - Filling options cartridge - bulk or filler nipple - Accepts standard 400g cartridges - Two hand operation

Part No.	Description	Price £
J1786004	Lever Grease Gun	12.60

Redashe® Lubeworks® Grease Control Gun



Features: Booster gun suitable for air powered grease units - Develops up to 600bar (8700psi) of pressure - Single hand operation - 1/4" female swivel inlet - Suitable for use with most types of air operated grease equipment

Part No.	Description	Price £
J1785701	Grease Control Gun	38.00

Redashe® Macnaught® Flexigun



Features: Short stroke operation - easily delivers up to 52-000kPa/7-500 psi/520 bar - Easy one hand operation - Flexible outlet with Supergrip KY Coupler - Filling Options: Bulk - Cartridge or J2 Grease Pump - Delivers 0.68gm per shot - Filler/bleeder nipple 1/4" BSP (M) - Fully repairable - Suitable for use with greases up to NLGI No. 2

Part No.	Description	Price £
K32	Flexigun	61.48

Redashe® Macnaught® Lever Grease Gun



Features: Rigid outlet with Supergrip KY Coupler - Filling Options: Bulk - Cartridge or J2 Grease Pump - Delivers up to 69-000kPa/10-000 PSI/690 bar grease pressure - Delivers 1.5gms per shot - Filler/bleeder nipple 1/8" BSP (M) - Fully repairable - Suitable for use with greases up to NLGI No. 2

Part No.	Description	Price £
K40	Lever Grease Gun	68.90

Redashe® Macnaught® Grease Pump



For fast and easy loading of grease guns and the Mini-Lube refillable container KT5. The J2 Grease Pump enables you to buy grease more economically whilst the fully sealed system keeps out any contaminants - Features: Transfer Grease Pump fills K29 - K32 - K40 - K45 - K53 and KT5 (for the K6 mini-lube) - Fully sealed system keeps grease clean - Rubber edged follower provides wipe down of container walls - Models available to suit 12.5kg (28lb) to 22kg (48lb) containers - Delivers 54gms per stroke - Redashe list the standard UK model suitable for use with 12.5kg grease kegs

Part No.	Description	Price £
J2	Grease Pump	206.70

Redashe® Lubeworks® Air Operated Grease Pump Kit



There are two grease pump kits available, the J1700512 suitable for use with standard UK size 12.5kg kegs, and the J1700524, which is suitable for use with standard UK size 50kg kegs. Both of these robust, efficient, trouble free units are supplied complete with pump, lid, follower plate, 4mtr of hose 'z' swivel, and grease delivery gun. A wheel-mounted trolley is available as an optional extra, part No J1708001. Features: Precision machined to ensure stability and long life - Supplied complete with: - 4mtrs hose; booster gun; 'z' swivel; lid; follower Plate. 360 deg 'z' swivel for easy access.

Part No.	Description	Price £
J1700512	12.5kg Air Operated Grease Kit	280.00
J1700524	50kg Air Operated Grease Kit	290.00
J1708001	Optional Drum Trolley	61.00

Redashe® Macnaught® Power-Lube



Features: Up to 69-000kPa/10-000 PSI/690 BAR greasing pressure through B2 Booster Gun - Non-Corroding Air Motor – quiet operation - Air pressure range 400-850kPa/60-125 PSI/4-9 BAR - Rubber edged follower plate provides wipe down of container walls - Extra long delivery hose – 4m (13ft) x 6mm (1/4") I.D SAE 100 R2 - 1/4" NPT (M) - 360° high pressure "Z" type ZSB swivel - 1/4" NPT (F) - 1/8" BSP (M) - Handles up to NLGI No 2 greases - Requires air compressor volume 3cfm/.08m3 and above - Delivers 460gms of NLGI No 2 grease per minute - Swivel type air inlet 1/4" NPT (F).

Part No.	Description	Price £
P3	Power-Lube	620.10

Redashe® Macnaught® Mini-Lube



Features: Two speed KR grease gun delivers up to 69-000kPa/10-000psi/690 bar - Spring loaded pump provides 30 shots of grease - 1.5m (5ft) Delivery Hose - 360° swivel prevents the hose from kinking - Rubber edged follower provides wipe down of container walls - Fully sealed system keeps grease clean - Delivers approx 1.25gms on high volume switch - Delivers approx 0.45gm on high pressure switch - Suitable for use with greases up to NLGI No. 2 (fits 3kg tin)

Part No.	Description	Price £
K6	Mini-Lube	252.40

Redashe® Macnaught® Maxi-Lube



Features: Up to 69-000kPa/10-000 PSI/690 BAR greasing pressure through B2 Booster Gun - Non-corroding air motor – quiet operation - Air pressure range 400-850kPa/60-125 PSI/4-9 BAR - Rubber edged follower plate provides wipe down of container walls - Extra long delivery hose – 4m (13ft) to 6mm (1/4") I.D SAE 100 R2-1/4" NPT (M) - 360° high pressure "Z" type ZSB swivel - 1/4" NPT (F) - 1/8" BSP (M) - Handles up to NLGI No 2 greases - Requires air compressor volume 3cfm/.08m3 and above - Delivers 460gms of NLGI No 2 grease per minute - Swivel type air inlet 1/4" NPT (F).

Part No.	Description	Price £
P6	Maxi-Lube	746.10

Redashe® Macnaught® Super-Lube



Features: Two speed KR grease gun delivers up to 69-000kPa/10-000 PSI/690 bar - Spring loaded pump provides 60 shots of grease - 3m (10ft) Delivery Hose - 360° swivel prevents the hose from kinking - Rubber edged follower provides wipe down of container walls - Models to suit 12.5kg (28lb) to 22kg (48lb) pails - Fully sealed system keeps grease clean - Delivers approx 1.25gms on high volume switch - Delivers approx 0.45gm on high pressure switch - Suitable for use with greases up to NLGI No. 2

Part No.	Description	Price £
K3	Super-Lube	371.00

Redashe® Lubeworks® Z Swivel



Features: Allows full 360 degree rotation - 1/4" male & female - Fits grease control guns with 1/4" female inlets - Allows user the flexibility to grease in awkward areas

Part No.	Description	Price £
J1785702	Z Swivel	18.00

Redashe® Lubeworks® Hydraulic Coupler



Features: 4 Jaw coupler - Thread M10 - Safe working pressure 600bar/8-700psi - Designed to fit most grease nipples & grease guns

Part No.	Description	Price £
J1785701H	Hydraulic Coupler	1.55

Redashe® Lubeworks® Flexible Extension



Features: 300mm (12") flexible extension - Maximum working pressure 7000psi - Male threads on either end - Supplied with 4 jaw coupler

Part No.	Description	Price £
J1786004-1	300mm Flexible Extension	5.25

Redashe® Macnaught® Refillable Bearing Lubricators



Features: Manufactured from transparent Lexan - Setting dial (1 - 3 - 6 and 12 months) supply duration - Supplied with medium tension spring with optional light & strong tension springs available for varying applications - Operating temperatures -30°C to +132°C - Suitable for use with all types of grease NLGI 0-1-2-3-4 - Available in 100ml and 220ml sizes - Outlet Thread M10 with 1/8" BSP Adaptor.

Part No.	Description	Price £
MCGL100	100ml Refillable Bearing Lubricator	46.74
MCGL220	220ml Refillable Bearing Lubricator	53.42

Redashe® Lubeworks® Rigid Oil Control Gun



The J1782801 is a durable and lightweight oil control valve with rigid nozzle and manual tip - typical fluids handled are motor oil, gear oil, transmission fluids etc - Features: Inlet connections: 1/2" swivel female - Max pressure: 50 bar / 750 psi - Temperature: Max 60°C Spout - Rigid nozzle with manual tip

Part No.	Description	Price £
J1782801	Lubeworks: Rigid Oil Control Gun	42.86

Redashe® Lubeworks® Flexible Oil Control Gun



The J1782802 flexible oil control gun is a durable and lightweight oil control valve with flexible nozzle and automatic tip - typical fluids handled are motor oil, gear oil, transmission fluids etc - Features: Inlet connections: 1/2" swivel female - Max pressure: 50 bar / 750 psi - Temperature: Max 60°C Spout - Flexible nozzle - with automatic tip

Part No.	Description	Price £
J1782802	Lubeworks: Flexible Oil Control Gun	44.00

Redashe® Lubeworks® Digital Oil Control Gun



The J1781501F/R digital oil meter is a durable and accurate and supplied with both rigid and flexible nozzles - typical fluids handled are motor oil, gear oil, transmission fluids etc. Resettable total for daily, weekly and lifetime dispense reports with a 5-digit easy to read LCD display powered by 3V battery - Features: Inlet connection: 1/2" female - Fluid range: 1 - 35 l/min; 0.3 - 9.2 gpm - Low battery indicator - Pressure range: 0.5 -50 bar / 7 - 750 psi - Temperature - Max 60°C - Accuracy: +/- 0.5 % - Viscosity: 8 - 5000 mPas - Spout: Supplied with both rigid - and flexible nozzles - Power source: 1*3V CR2 Battery - Weight: 1.4 kg / 3 lb - Rubber protection cover.

Part No.	Description	Price £
J1781501F/R	Lubeworks: Digital Oil Meter	123.00

Redashe® Lubeworks® Digital Preset Oil Gun



The Lubeworks oil control gun PMG35A is a Electronic Preset meter. This control gun is suitable for use with engine oil - gear oil - automatic transmission fluid & anti-freeze/anti-boil - Features: 5 Digit LCD Display - In addition to the standard manual & auto mode functions - there are five pre-settable totals which can be changed for frequently required volumes - Automatic non drip nozzle - Shock resistant - 2-Year warranty

Part No.	Description	Price £
J18133502	Lubeworks: Digital Preset Oil Gun	214.20

Redashe® Macnaught® Oil Control Gun



Image For Illustration Purposes
Only - Shows Flexible Only

The MH40/MH50 is a low cost oil control gun with a fully integrated mechanical/LCD meter. Suitable for dispensing engine oil - gear oil - automatic transmission fluid and anti-freeze/anti-boil - with a maximum viscosity of SAE 140 - Features: Flexible extension - Meter with 4-digit resettable batch totalizer and 6 - digit accumulative totalizer - Protective shroud surrounding the meter - Robust aluminium handle with plastic trigger and guard - Dispenses up to 30l per minute (8 US gal per min) - Automatic non-drip nozzle.

Part No.	Description	Price £
MH40R-01	Mech Oil Control Gun (Rigid)	275.00
MH50R-01	Digital Oil Control Gun (Rigid)	305.00
MH40F-01	Mech Oil Control Gun (Flexible)	275.00
MH50F-01	Digital Oil Control Gun (Flexible)	305.00

Redashe® Lubeworks® Lever Hand Pump



The J1703001 self-priming lever pump is manufactured in steel - which is zinc-plated to give a quality finish. Supplied with self-adjusting - telescopic suction tube and 2" bung nut - Features: Cushioned vinyl handle - Supplied with self adjusting suction tube - Dispenses approximately 300cc per stroke - Zinc plated for lasting quality and appearance - Suitable for use with 50-205ltr drums

Part No.	Description	Price £
J1703001	Lever Hand Pump	21.00

Redashe® Lubeworks® Rotary Barrel Pump



The J1703004 rotary action vane type pump is suitable for dispensing diesel - and lubricating oils up to SAE 90 - output of up to 25litres per minute - Features: Supplied with 3 piece suction tube and 2" bung adaptor - Built in suction strainer.

Part No.	Description	Price £
J1703004	Rotary Barrel Pump	22.05

Redashe® Lubeworks® 1:1 Air Operated Oil Pump With 940mm Suction Tube



Redashe pneumatic oil pumps are designed and constructed to give outstanding performance in all workshop environments. A full range of pumps is available to cover every type of application in the Automotive, Agricultural, commercial vehicle, and heavy plant workshops. Low noise level air motors are used that will provide years of trouble free service. Typically used in workshops, service stations, fast lube centers, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.

Part No.	Ratio	Working Pressure	Max. Fluid Pressure	Output Capacity ltr./min.	Suction Tube Dia.	Max. Viscosity	Price £
J100	1:1	5-8 Bar (70-115psi)	8 bar (115 psi)	18 L/Min	42mm	120 SAE	170.00

Redashe® Lubeworks® 3:1 Air Operated (Stubby) Oil Pump



Redashe pneumatic oil pumps are designed and constructed to give outstanding performance in all workshop environments. A full range of pumps is available to cover every type of application in the Automotive, Agricultural, commercial vehicle, and heavy plant workshops. Low noise level air motors are used that will provide years of trouble free service. Typically used in workshops, service stations, fast lube centers, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.

Part No.	Ratio	Working Pressure	Max. Fluid Pressure	Output Capacity ltr./min.	Suction Tube Dia.	Max. Viscosity	Price £
J300S	3:1	5-8 Bar (70-115psi)	24 bar (350 psi)	12 L/Min	42mm	150 SAE	160.00

Redashe® Lubeworks® 5:1 Air Operated (Stubby) Oil Pump



Redashe pneumatic oil pumps are designed and constructed to give outstanding performance in all workshop environments. A full range of pumps is available to cover every type of application in the Automotive, Agricultural, commercial vehicle, and heavy plant workshops. Low noise level air motors are used that will provide years of trouble free service. Typically used in workshops, service stations, fast lube centers, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.

Part No.	Ratio	Working Pressure	Max. Fluid Pressure	Output Capacity ltr./min.	Suction Tube Dia.	Max. Viscosity	Price £
J500S	5:1	5-8 Bar (70-115psi)	40 bar (584 psi)	14 L/Min	42mm	240 SAE	175.00

Redashe® Lubeworks® Pneumatic Oil Dispenser



The JPOD030/065 are suitable for filling and topping up of oil - once charged the unit can be used without being connected to the air supply - and is equipped with a level gauge delivery gun and flexible hose. Will dispense all automotive engine and gearbox oils - Features: Pneumatic oil dispenser equipped with level gauge and delivery gun with flexible end - Works autonomously with out the requirement of continuous connection to air supply

Part No.	Description	Price £
JPOD030	30ltr Pneumatic Oil Dispenser	160.00
JPOD065	65ltr Pneumatic Oil Dispenser	192.00

Redashe® Lubeworks® Pneumatic Oil Pump Kit



Features: Suitable for use with oils up to 120SAE - Suitable for use with engine oil - synthetic oil - hydraulic oil - gear oil & ATF - Supplied with 2" bung adaptor - Kit includes 1:1 drum pump - bung adaptor - FRL - 3m (10ft) reinforced oil delivery hose & oil dispensing gun

Part No.	Description	Price £
J100TDG	Pneumatic Oil Pump Kit	298.00

Redashe® Lubeworks® Mobile Oil Dispensing Kit



Mobile oil dispensing units for 205 Litre Barrels - suitable for dispensing oil at medium/high viscosity - for mobile installations and fixed system at medium distances - the drum trolley allows the system to be moved around the workshop with ease - giving increased efficiency. All items are available separately or in kit form - Features: Suitable for use with 205 litre drum - Supplied complete with a 3 : 1 ratio pump - digital control oil gun - trolley and connection hose.

Part No.	Description	Price £
JOS200	Mobile Oil Dispensing Kit	695.00

Redashe® Lubeworks® Wall Mounted Oil Dispensing Kit



The C808-MODK Modular oil dispensing kit is suitable for oil tanks and drums with the option of mounting the pump to the wall. The kit includes the popular 808 series medium pressure oil reel - along with a choice of 1:1 - 3:1 or 5:1 ratio oil pumps - connecting hose. Included will also be the J1781501 Lubeworks® Digital Oil Gun and wall mounted pump bracket and the JDT10001 drip tray.

Part No.	Description	Price £
C808MODK	Wall Mounted Oil Dispensing kit	570.00

Redashe® Lubeworks® Air Operated Oil Drainer



Designed to drain - by gravity - waste oil from engines - gear boxes and differentials of all vehicles. The emptying of the drained oil inside the reservoir is air operated - Features: Air operated oil drainer with centre mounted adjustable collecting bowl - Adjustable collecting bowl height to work with jack - lift or servicing cock - Equipped with a valve for collecting bowl to inspect drained oil before it enters the reservoir - Can be equipped with a special support to allow filters to drain

Part No.	Description	Price £
JAOD3090	90ltr Gravity Drainer	215.00

Redashe® Lubeworks® Aluminium Delivery Nozzle



Aluminium Diesel Delivery Nozzle with cast aluminium body and 3/4" inlet port - suitable for use with gravity or pumped systems - integral hook for easy storage when not in use - Features: Suitable for use with pumped and gravity flow systems - Integral hook for easy storage when not in use - 3/4" Inlet port - Maximum flow rate 60Lpm

Part No.	Description	Price £
J1789021	Lubeworks: Aluminium Delivery Nozzle	24.15

Redashe® Lubeworks® Auto Shut Off Nozzle



Constructed in cast aluminium with plastic coated body and plastic handle assembly. The J1789022 automatically shuts off the flow of fuel when the tank is full - Features: Flow rate 45-60 Lpm - 3/4" swivel inlet - High - medium and low volume latching facility - Suitable for use with Petrol or Diesel - Integral strainer - Plastic coated body and plastic handle assembly - Automatically shuts off the fuel flow when the tank is full.

Part No.	Description	Price £
J1789022-1	Lubeworks: Auto Shutoff Nozzle	38.85

Redashe® Lubeworks® High Volume Auto Nozzle



Constructed in cast aluminium with plastic coated body and handle assembly. The J1789023 automatically shuts off the flow of fuel when the tank is full - Features: Flow rate 80 – 120Lpm - High - medium and low volume latching facility - 1" inlet with 1" spout - Suitable for use with Petrol or Diesel - Plastic coated body and handle assembly - Automatically shuts off the fuel flow when the tank is full.

Part No.	Description	Price £
J1789023-1	Lubeworks: High Volume Auto Nozzle	59.85

Redashe® Lubeworks® Fuel Transfer Pump



This robust self-priming vane type diesel pump is housed in its own neat and compact cabinet - and delivers up to 45L of diesel per min. The pump motor is continuously rated with a thermal cut-out - the unit is supplied with - mechanical meter with a 4 digit resettable totaliser - and 8 digit non resettable totaliser - Features: Medium output – 45 Litres pm - Pump and meter housed in painted Steel cabinet - 230v single phase motor with IP45 protection - Self priming vane type pump - Continuous duty cycle with thermal overload cut out - Meter accurate to +/- 1% - Supplied complete with 4mtr of delivery hose and automatic nozzle - Inlet connection 1" - Outlet connection 3/4"

Part No.	Description	Price £
J1500450	Lubeworks: Fuel Transfer Pump	396.90

Redashe® Lubeworks® Fuel Transfer Pump



This robust self-priming vane diesel pump delivers up to 45L/m - The pump motor is continuously rated with a thermal cut-out - mechanical meter with a 4 digit resettable totaliser - and 8 digit non resettable totaliser - Features: Medium output – up to 45L/min - Self priming vane type pump - Continuous duty cycle - Thermal overload cut out - Inlet connection 1" - Outlet connection 1" - Meter accurate to +/- 1% - Supplied complete with 4mtr of delivery hose and automatic nozzle.

Part No.	Description	Price £
J1500451	Lubeworks: Fuel Transfer Pump	349.65

Redashe® Lubeworks® Mechanical Fuel Meter



This mechanical fuel meter has a flow rate of 20-120 ltrs per minute - with a resettable 4-digit totaliser - and a non-resettable 8-digit totaliser - which registers up to 9-999-999.9 Litres. Suitable for use with diesel - Features: Aluminium-metering chamber with polybutylene nutating disk - Flow rate 20 – 120ltrs per minute (5-30gpm) - 1" inlet / outlet - Accuracy +/-1% - Maximum working pressure 3.5bar / 50psi.

Part No.	Description	Price £
J1581400	Lubeworks: Fuel Meter	75.60

Redashe® DM100 Diesel Flowmeter



Suitable for diesel - kerosene and petrol - the DM100 is specifically designed for the accurate measurement of fuels in non-resale applications. Manufactured from corrosion resistant materials the DM100 uses oval gear technology to deliver 1% accuracy with low pressure drop making it suitable for gravity and pumped applications at up to 80 litres per minute. The mechanical register - which can be rotated in 90 degree steps - features a 6 digit non-resettable and 4 digit push button resettable display - Features: In-built wire mesh strainer - Rotatable large digit mechanical display - 10 year guaranteed parts availability.

Part No.	Description	Price £
DM100	Macnaught: Flowmeter	238.50

Lubrication & Fuel Systems

Economy Side Lever Grease Gun Kit



Lubrication & Fuel Systems - Kit Comprising Of 400cc Side Lever Grease Gun - With Rigid Stem & Hydraulic Connector - Working Pressure: 2000psi

Part No.	Description	Price £
GGUN01	400cc Grease Gun With Rigid Tube & Connection	13.82

Side Lever & Pistol Grease Guns



Lubrication & Fuel Systems - Choose side lever or pistol/one handed grease gun - Cast head & steel barrel - Accepts either 400cc/500cc cartridges or bulk grease - Supplied c/w cranked rigid & flex spout & 4 jaw connector - Bulk filling nipple - Plastic handle grip for comfortable usage - Weight 1.60 kg

Part No.	Description	Price £
GR.G3	Side lever grease gun	20.56
GR.G6	Pistol/one handed grease gun	33.30

12V Grease Gun Kit - Cordless



Lubrication & Fuel Systems - Suitable for use with grease cartridges or bulk fill - 12V rechargeable & lightweight - 240V AC adaptor & lead for recharging from the mains - Will dispense upto 4 grease cartridges on one charge - Includes grease gun, flexi-hose, battery & charger Protective carry case - Supplied with spare battery - Maximum Operating Pressure: 5800psi (400bar)

Part No.	Description	Price £
GR.12V	12V grease gun kit	210.23

Industrial Side Lever Grease Gun



Lubrication & Fuel Systems - Fitted With Air Bleed Valve Capable Of Generating 7000psi Of Pressure

Part No.	Description	Price £
GGUN02	500cc Grease Gun Body	27.73

Air Operated Grease Gun



Air Operated Grease Gun - Pistol grip/one handed air operated (can also be manually operated) - Accepts either 400cc/500cc cartridges or bulk grease - Bulk filling nipple. Kit includes: - Manual side lever grease gun head - Rigid & 300mm flexible spout & 2 x 4 jaw connectors - Quick release airline fittings

Part No.	Air Pressure Required	Max Operating Pressure	Price £
GR.GAIR	30 - 45 psi (2-3 bar)	6000 psi (400 bar)	23.00

4 Jaw Hydraulic Connector



Lubrication & Fuel Systems - For Use With Standard HI Grease Nipples

Part No.	Type	Price £
GEXT03	Connector	2.72

Bent Rigid & Hydraulic Connector



Lubrication & Fuel Systems

Part No.	Description	Price £
GEXT01	6" Connector Tube	3.70

Nylon Flexible Tubes



Lubrication & Fuel Systems - Flexible Tubes With 1/8" BSP Male Threaded Ends

Part No.	Type	Price £
GEXT02	12" Long Nylon Tube	4.35

Hook On Connector



Lubrication & Fuel Systems - For Use With Standard Tat Head Nipples

Part No.	Type	Price £
GEXT04	Connector	6.06

High Pressure Nylon Flexible Tube



High Pressure Nylon Flexible Tube - Applications: Automatic Lubrication Systems - Piping Out Inaccessible Grease Points - Colour: Black

Part No.	Tube O.D	Coil	Burst Pressure (Bar)	Price £
INTH03BL	3/16"	30m	150	44.46
HPP6-1.5	6mm	25m	150	26.25

High Pressure Braided Flexible Pipe



High Pressure Braided Flexible Pipe - Description: High Pressure Hose (Supplied In 25m Coils) - Re-Usable Sleeve (Two Per Hose Required) - Re-Usable Stud (Two Per Hose Required) - Applications: For Main Feed Lines In Lubrication Systems - For Moving Points

Part No.	Description	Price £
BRH8.6-1M	High Pressure Hose - 25m	3.24
SRST	Re-Usable Stud (Steel Plated)	1.65
SRSS	Re-Usable Sleeve (Steel Plated)	1.55

Grease Gun Filler Pump



Grease Gun Filler Pump - For filling grease guns with bulk grease - Fits onto 12.5kg grease gun kegs - Enables you to buy bulk grease saving money - Specifications: Low pressure - hi volume grease pumps - 1.2m outlet hose & quick release female connector

Part No.	Price £
GR.GGFILL.L	81.15

Portable Grease Dispenser



Lubrication & Fuel Systems - 50:1 ratio grease pump - 2 wheeled trolley - 4m of 1/4" bore delivery hose - Grease gun complete with straight swivel - 385mm diameter drum cover - 370mm diameter follower plate - Fits 50kg grease keg

Part No.	Description	Price £
GR.AM50C	Air operated grease pump kit	470.00

Manual Oil Delivery Nozzle



Manual Oil Delivery Nozzle - ONLY Suitable For Oils - Supplied With Flexible Spout And Anti Drip Tip - 1/2" BSPF Swivel Inlet - Max. Pressure 1015psi (70bar)

Part No.	Price £
NOZ.OEC	59.00

Digital Hose End Oil Meter



Lubrication & Fuel Systems - Only suitable for use with lubricating oils - Manual or pre-selection options - Supplied with flexible spout & anti drip tip - 6 digit non resetable totaliser - Battery Operated (4xAA batteries supplied) - LCD display - 4x11.5mm high digits - Accuracy +/- 0.5% - Weight 1.40 kg - 1/2" BSPP Female Swivel Inlet - Maximum Pressure: 994 psi (70 bar) - Flow Rate: 1 - 30Ltrs/min

Part No.	Description	Price £
OIL-M10C	Digital hose end oil meter/ nozzle	175.99

Mains Transfer Pump For Oil



Lubrication & Fuel Systems - Only suitable with Diesel or Bio-Diesel up to B100 & clean oils up to SAE 90 - Eccentric pump unit - Switch & bypass valve - 3/4" BSPP ports fitted with 1" hoses - Foot mounting plate. Weatherproof to IP55 - Continuously rated motor with thermal cut out - Weight 8.45 kg - Maximum Flow Rate: 20Ltrs/min (SAE 30 @ 20°C) - Maximum Suction Lift: 1m

Part No.	Description	Price £
OIL.GEL220	230V oil pump 3/4" bsp female inlet/outlet ports	465.00

Oil Drain Pans

OPAN6



OPAN14



Oil Pan Polyethylene - Suitable for single or multiple oil changes - Made from UV stable polyethylene - 6 or 14 litre with pouring spout.

Part No.	Description	Price £
OPAN6	6 Litre Drain Pan	2.97
OPAN14	14 Litre Drain Pan	13.38

Mobile Oil Dispenser



A complete mobile oil dispensing system suitable for use with engine - hydraulic - synthetic - gear & transmission oils - Features: 3:1 air operated oil pump with 940mm suction pipe - Supplied with digital hose end meter - Supplied with 4m x 1/2" bore oil hose - Supplied with heavy duty 4 wheel trolley - Optional 15m x 1/2" fixed bracket open oil hose reel (part number AOP.3T.HR.A).

Part No.	Description	Price £
AOP.3T.HR.A	With Hose Reel	761.54
AOP.3T.A	Without Hose Reel	527.69

Gravity Drainer



Lubrication & Fuel Systems - Ideal for gravity draining of engine, gearbox and differential oils - Used to drain oils from all motor vehicles on auto lifts or pits - 13 litre collection bowl is height adjustable - 90 litre tank capacity - Equipped with level gauge - Oversize funnel anti splash screen - Removable tool tray

Part No.	Description	Price £
WODHL.90C	Waste oil drainer	408.27

Hose Reel For Oil



Hose reel open - 15m x 1/2" - 138 bar - c/w swivel/fixed bracket - Lubeworks 870 series oil reel - Spring rewind. Heavy duty steel construction - powder coated - Fully adjustable hose stop - Supplied with 15m x 1/2" BSPM hose & 600mm flexible inlet hose - Fixed & swivel mount bracket supplied.

Part No.	Price £
HRO15.12C	259.25

Manual Nozzle



Lubrication & Fuel Systems - Only suitable with Diesel or Biodiesel up to B100 - 1" BSPP Female Swivel Inlet - Cast aluminium body - Can be used with gravity feed tanks or Electric Pumps - Integral hook for tidy storage when not in use - Flow Rate: 80 Ltrs/min - Maximum Pressure: 3.5 bar (50 psi) - Manual Gravity Feed Nozzle

Part No.	Description	Price £
NOZ.S2A	Manual Diesel Nozzle	21.89

Professional Automatic Nozzle



Lubrication & Fuel Systems - Only suitable with Diesel or Bio-Diesel up to B100 - 1" BSPF Female Swivel Inlet Automatically shuts-off the flow of fuel when vehicle tank is full - 3 position stay open latch, which may be disabled if required - For use with electric pumps only

Part No.	Description	Flow Rate (Ltrs/min)	Pressure (bar)	Pressure (psi)	Price £
NOZA.X	Automatic Nozzle	10-80	0.5-4	7-58	95.55
NOZA.X25	Automatic Hi-Speed Nozzle	80-140	0.5-3.5	7-50	159.49

1" Flow Meter



Lubrication & Fuel Systems - Only suitable for use with Diesel - Robust nutating disc flowmeter shows up to 999 litres - 1" BSPF ports. Accuracy of +/- 2% with adjustable calibration - Robust housing & cover 4 digit register. 8 digit non-resettable totaliser - Front face can be rotated in 90 degree increments - Weight 2.02 kg - Flow Rate: 20 - 80L/min. - Maximum Pressure: 50 psi (3.5 bar)

Part No.	Description	Price £
FM4	4 digit flow meter - 1"bsp female ports	124.48

Goodyear Soft Wall Fuel Dispensing Hoses



Lubrication & Fuel Systems - Only suitable with Diesel or Bio-Diesel up to B100 - Ideal for use on economy fuel dispensers. Machine swaged ends for long life. (Electrically bonded) - NOT steel braided - Max Pressure: 50 psi (3.5 bar) - NOT suitable for use with petrol

Part No.	Description	Price £
CH4.19	4m Hose Assembly with 3/4" BSPT Male End Fittings	45.57
CH6.19	6m Hose Assembly with 3/4" BSPT Male End Fittings	60.45
CH4.25	4m Hose Assembly with 1" BSPT Male End Fittings	53.79
CH6.25	6m Hose Assembly with 1" BSPT Male End Fittings	73.98

Compact Cabinet Pump



Lubrication & Fuel Systems - Suitable for pumping diesel & gasoil - 230V self priming pump - 4 digit flowmeter - 4m delivery hose - Integral suction valve & strainer - Automatic nozzle - Wall mount or tank mount - Weight 20.00 kg - Flow Rate: 45Ltrs/min

Part No.	Description	Price £
BOX45	230V diesel pump kit c/w meter & delivery/suction hose	528.00

Portable Diesel Kit



Lubrication & Fuel Systems - Suitable for pumping diesel - Carry handle. On/off switch & bypass valve - 4m long battery lead & crocodile clips - 6m suction/delivery hose with manual nozzle - Suction foot valve & strainer must be fitted or warranty void - Max. Run time 30 mins - Weight 8.6 kg

Part No.	Description	Price £
12PA.KIT1B	12V diesel pump kit	189.06
24PA.KIT1B	24V diesel pump kit	189.06

Syphon Pumps



Lubrication & Fuel Systems - Suitable for pumping most liquids, acids, alkalies, antifreeze, de-greaser, distilled water, diesel, biodiesel B100, light oils & solvents - Includes delivery hose & suction pipe

Part No.	Description	Price £
HPS25	Syphon Pump Fits 5-25L Containers. Delivery Hose 534mm (21) - Suction - 380mm (15)	3.75
HPS205	Syphon Pump Fits 250L Containers. 2 BSPT Male Thread. Delivers 30ltrs/min. Delivery Hose 1295mm (51) - Suction - 850mm (33.5)	14.37

Lever Hand Pump



Lubrication & Fuel Systems - Suitable with Diesel, Bio-diesel up to B30 or oils to SAE 90 - Metal lever action drum pump - Capable of up to 16L/min - 2" BSPT male drum adaptor - Telescopic suction pipe - Ideal for trade counter display - Weight 2.17 kg

Part No.	Description	Price £
LEVER.S	Lever Action Hand Pump	30.51

Rotary Drum Pump



Lubrication & Fuel Systems - Suitable with Diesel, Bio-diesel up to B30 or oils to SAE 90 - Compact version cast iron rotary action drum pump - 3 piece suction pipe c/w mesh - Capable of up to 25Ltrs/min - 2" BSPT male drum adaptor Ideal for trade counter display - Weight 5.10 kg

Part No.	Description	Price £
MSS21	Rotary Action Hand Pump	34.74

Liquid Extraction Vacuum Pump



Lubrication & Fuel Systems - Suitable for fuels, water, oils and many other liquids. Removes oil from vehicles, lawnmowers & motor bikes without draining, simply insert suction pipe in dipstick hole. Can remove water from bonded fuel tank cabinets & suck up any fuel spillages. (Holds up to 6 litres). Novel device that both sucks & stores extracted liquids. Lightweight & portable with a capacity of 6 litres. When full, remove top plug to pour out the contents. Supplied with two suction pipes to fit most applications. Removes water from fish tanks, bilges & inaccessible areas. Weight 2.96 kg.

Part No.	Description	Price £
HP.SUC6	Liquid Extraction Pump	89.22

Lift Pump Polypropylene



Lift pump c/w accessories (no hose) - Suitable with diesel - biodiesel up to B100 or oils to SAE 90 - Lift pump manufactured from polypropylene with viton seals - Dispenses approximately 250ml per stroke - Fits 20 - 25L & 205L containers (2 piece adjustable suction tube) - Outlet spout can be removed to reveal 3/4" BSP (19mm) hose tail - Supplied with two adaptors: - One fits most 25L external Plysu (60mm dia) - The other fits most 25L Trisure/Valorex thread (56mm dia) - Also fits 205L drums with a 2" BSP internal thread - Option universal adaptor - locks onto any external thread (AD.UNI).

Part No.	Price £
HPLP	37.69

Semi Rotary Pumps



Lubrication & Fuel Systems - Suitable with Diesel, Bio-Diesel up to B100, light oils & water - Semi rotary double acting - Cast iron body with brass internals - Flanged inline threaded ports - Choose from: 1/2" K0 version 11Ltrs/min, 3/4" K1 version 17Ltrs/min, 1" K2 version 22Ltrs/min - All with 7m Suction Lift - BSPP Female Thread - Weight from 5.10 - 8.80 kg depending on size

Part No.	Description	Price £
SRG0A	Semi rotary hand pump 1/2" (K0)	67.10
SRG1A	Semi rotary hand pump 3/4"(K1)	68.58
SRG2A	Semi rotary hand pump 1" (K2)	78.18

Mains Diesel Transfer Pump



Lubrication & Fuel Systems - Only suitable with Diesel or Bio-Diesel up to B100 - 230V Direct drive, self priming, vane pumping unit - 1" BSPP Female ports - Switch & 2m long mains cable - Integral filter & bypass - Weatherproof to IP55 for outdoor use - Continuously rated motor with thermal cut out - Weight 16.64 kg - Flow Rate: 50ltrs/min

Part No.	Description	Price £
SPT70K	230V diesel pump	224.23

1" Engine Driven Transfer Pump



Lubrication & Fuel Systems - Only suitable for transferring Diesel or Clean Water - Maximum Flow 125Ltrs/min. - 1.6 litre unleaded petrol tank - Total head 20 metres - Suction lift 9 metres - 4 stroke engine with recoil start - 1" hose tails & suction strainer - Dimensions: 470mm H x 450mm W x 320mm D - If used with nozzle/valve as means of control, a pressure relief valve must be used or warranty void - Weight 17 kg

Part No.	Description	Price £
EDP150A	Petrol engine driven pump for diesel or water	363.50

1" Suction Hose



Lubrication & Fuel Systems - Only suitable with Diesel or Bio-Diesel up to B100 - Flexible PVC with rigid spiral embedded compound - 1" (25mm) I/D - Options: End Fittings and Clips Available - Maximum Pressure: 9.0 bar (130.0 psi)

Part No.	Description	Price £
SH25.10	10m Hose Suitable For Diesel (No Ends)	129.60
SH25.30	30m Hose Suitable For Diesel (No Ends)	234.56

Diesel Driven Pump



Diesel Driven Pump - Pumps up to 600 litres per minute - Dimensions: 600mm H x 530mm W x 450mm D - Total head 27m - suction lift 8m - Dry weight 41kgs - 12.5L fuel tank - Direct Delivery From Manufacturer.

Part No.	Description	Price £
EDP500DA	For Pumping Bio Diesel	670.62
EDP500DW	For Pumping Water (Clean)	615.23

Drum Taps - Brass



Lubrication & Fuel Systems - Robust brass drum tap with nickel plated finish - Lift hasp & turn to open 3/4" - BSPM thread inlet & outlet - May be padlocked in the closed position - Outlet spigot can accept hose

Part No.	Description	Price £
DT3H	Brass drum tap nickel plated	10.57

Hose Reel For Diesel



Hose Reel For Diesel - Self retracting spring rewind powder coat reel fitted with 8m x 1" diesel hose with 1" male ends - Max Pressure 6 bar - Can be used with pumps up to 70L/min. (20% flow restriction) - 8m of 1" hose already fitted to the reel - with 1m inlet hose. Max. pressure 90 psi (6 bar)

Part No.	Price £
HRO8.25	800.00

Drum Taps - Polyethylene



Lubrication & Fuel Systems - Use with a wide range of oils, acids & caustics - Huge 2" version can be used for thick liquids - 2" version is also useful to empty drums fast or as a drum vent - BSPT male threads with sealing washer - Turn to open, turn back to close - Stay open operation, no locking facility - Choose 3/4" or 2" versions - Weight 0.19kg

Part No.	Description	Price £
DT3P	Polyethylene Drum Tap 3/4"	3.53
DTJ	Polyethylene Drum Tap 2"	29.34

Thread sealant 140ml for B85 - E85 & diesel



Thread sealant 140ml for B85 - E85 & diesel - Designed for ethanol blended petrol E10 – E85 blends - Also suitable for use with kerosene - diesel - propane - butane - LPG - cutting oil - ammonia - aliphatic solvents - acids - steam & potable water - UL classified - Temperature range –100°F to 800°F (-74°C to 318°C)

Part No.	Price £
GASOILA	53.85

GREASE NIPPLE STRAIGHT - STEEL



Lubrication & Fuel Systems - Straight - Steel BS1486 or DIN 71412 - Zinc Plated and Passivated

Part No.	Thread	Price £
GN02	1/8" BSPT	0.23
GN04	1/4" BSPT	0.53
GNM6	M6X1	0.22
GNM8	M8X1	0.24
GNU04	1/4" UNF	0.22

12V Compressor Kit - Standard Speed



Lubrication & Fuel Systems - For inflating tyres Inflates a 265/75R16 tyre in approx 3 mins (from 15 - 32 psi) - Direct battery connection - 3m lead & crocodile clips included - 8m coiled air outlet hose with quick connector & pressure gauge - Includes carry case & bike tyre/ball/inflatable adaptors - 12V, 23 amps, thermal overload protection - Weight 3.60 kg - Maximum Flow: 35Ltrs/min

Part No.	Description	Price £
COMP.12KIT	Standard speed compressor kit	61.18

GREASE NIPPLE 45° ANGLE - STEEL



Lubrication & Fuel Systems - 45° Angle - Steel

Part No.	Thread	Price £
GN0245	1/8" BSPT	0.46
GN0445	1/4" BSPT	0.84
GNM645	M6X1	0.44
GNM845	M8X1	0.44

12V Compressor Kit - High Speed



Lubrication & Fuel Systems - For inflating 4WD vehicles & tractors tyres - Inflates a 10R.15 off road tyre in approx 1 min (from 15 - 32 psi) - 8m coiled air outlet hose with quick connector & pressure gauge - Includes carry case & bike tyre/ball/inflatable adaptors - 12V, 30 amps, thermal overload protector - 3m lead & crocodile clips included - Direct battery connection - Weight 4.0 kg. - Maximum Flow Rate: 85L/min

Part No.	Description	Price £
COMP.12KITH	High speed compressor kit	80.90


GREASE NIPPLE 90° ANGLE - STEEL



Lubrication & Fuel Systems - 90° Angle - Steel

Part No.	Thread	Price £
GNM690	M6X1	0.44
GNU0490	1/4" UNF	0.44

GREASE NIPPLE TAT HEAD - STEEL



Lubrication & Fuel Systems - Tat Head - Steel Double Hex

Part No.	Thread	Price £
GNTH02	1/8" BSPP	0.59
GNTH04	1/4" BSPP	0.62

Box Of Assorted Grease Nipples



Grease Gun Accessories - 150 assorted straight & angled (BSP/BSF/UNF) - Housed in a handy box with compartments

Part No.	Measurement	Price £
GR.NIPI	Imperial	30.08
GR.NIPM	Metric	30.08

GREASE NIPPLE - STRAIGHT - STAINLESS STEEL 304



Lubrication & Fuel Systems - Straight - Stainless Steel 304

Part No.	Thread	Price £
SSGN02	1/8" BSPT	1.99
SSGNM6	M6X1	1.45

Grease Nipple Covers



Grease Nipple Covers - Colour: Red

Part No.	Price £
PNR	0.44

GREASE NIPPLE - TAT HEAD - STAINLESS STEEL 304



Lubrication & Fuel Systems - Tat Head - Stainless Steel 304

Part No.	Thread	Price £
SSGNTH02	1/8" BSPT	5.75

Food Lube Grease - White



Lubrication & Fuel Systems - For Use In Food Processing Environments

Part No.	Description	Price £
GREASE02	Grease 400g	6.42



Find
Tubes & Hoses
In
Section 1 & 16



Straight Male Connector - Adaptor



Straight Male Connector - Adaptor - Steel

Part No.	Thread Size	Tube O/D in MM	Price £
SMF04U/02	1/4 UNF (M)	1/8	2.17
SMFM6/02	M6X1(M) Taper	1/8	4.30
SMFM8/02	M8X1(M) Taper	1/8	4.30

Battery Plate Adaptor - Brass



Battery Plate Adaptor - Brass

Part No.	BSPF Female Thread (A)	Length	Tube O/D in MM (B)	Max Plate Thickness in MM	Clearance Hole in MM	Price £
BPAM02-06-1	1/8	41	6	13	11.50	3.89
BPAM02-06-2	1/8	48	6	19	11.50	4.49
BPAI02-03-1	1/8	38	3/16	8	10.00	3.35
BPAI02-03-2	1/8	44	3/16	14	10.00	3.98

Straight Male Connector



Straight Male Connector - Steel

Part No.	Thread Size in BSP/MM	Tube O/D in MM	Price £
SCMM6/02	1/8	6	2.22
SCMM6/06	6X1	6	2.22
SCMM8/06	8X1	6	2.28

Lithium EP2 Grease



Lubrication & Fuel Systems - This Is Formulated For General Purpose Lubrication EP2 - Suitable For Industrial Applications

Part No.	Description	Price £
GREASE01	All Purpose Grease 400g	2.95

Straight Coupling



Straight Couplings - Steel

Part No.	Tube O/D in MM	Price £
SC06	6	3.59

90° Compression Fitting



90° Compression Fitting - Steel

Part No.	Thread Size in MM	Tube O/D in MM	Price £
SEL02/06	1/8	6	5.34
SELM6/06	M6X1(M) Taper	6	4.88
SELM8/06	M8X1(M) Taper	6	4.85

Tee Connector

Tee Connector - Steel

Part No.	Tube O/D in MM	Price £
SCMT06	6	8.06

Universal Anchor Block

Universal Anchor Block - Material: Steel - Finish: Plated - Can Be Mounted Horizontal Or Vertical

Part No.	NPT Female Thread	Price £
81583-B	1/8	12.62

Anchor Block (One Way)

Anchor Block (One Way)

Part No.	BSPP Female Thread	Dimensions (A)	Dimensions (B)	Dimensions (C)	Price £
ABS02-1	1/8	30	15	15	5.67

Multi Point Anchor

Multi Point Anchor - Material: Steel - Finish: Plated

Part No.	BSPP Female Thread	Length	Ports	Price £
ABS02-2	1/8	62	2	7.88
ABS02-3	1/8	86	3	8.88
ABS02-4	1/8	108	4	9.59
ABS02-5	1/8	132	5	11.03
ABS02-6	1/8	154	6	11.89

For an extensive range of

Brass Fittings

see

section 8