

1/2" System

Temperature Range: 80°C (max) - Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile

• NV: Non Valve • V: Valve

Male Coupling



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile NV: Non Valve V: Valve

Part No.	BSPP Male Thread	Price £
NCM08/08	1/2" NV	8.28
NCM12/08	3/4" NV	8.06
NCM08/08V	1/2" V	15.01

Hose Tail Coupling



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Hose I/D	Price £
NCH06/08	3/8" NV	7.20
NCH08/08	1/2" NV	6.55
NCH12/08	3/4" NV	7.42
NCH08/08V	1/2" V	15.00
NCH12/08V	3/4" V	22.50

Female Coupling



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile NV: Non Valve V: Valve

Part No.	BSPP & Metric Thread	Price £
NCF08/08	1/2" NV	6.98
NCF12/08	3/4" NV	7.49
NCF08/08V	1/2" V	13.95
NCFM22/08V	M22x1 V	10.95

Female Plug



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Thread	Price £
NPF08/08	1/2" BSPP	3.05
NPF12/08	3/4" BSPP	4.43
NPFM22/08	M22x1	1.95

Male Plug



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Thread	Price £
NPM06/08	3/8" BSPP	2.95
NPM08/08	1/2" BSPP	2.95
NPM12/08	3/4" BSPP	3.24

Hose Tail Plug



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Hose I/D	Price £
NPH06/08	3/8"	2.81
NPH08/08	1/2"	3.39
NPH10/08	5/8"	2.55
NPH04/08	1/4"	2.88

Equal Plug



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Type	Price £
NPE08	Equal Plug	4.95

Double Hose Tail Plug



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Hose I/D	Price £
NPH12/08/08	3/4" & 1/2"	3.89

Spray Nozzle



Washdown Fittings 1/2" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile 15 & 20mm Hose

Part No.	Hose I/D	Price £
NSNH12/08/08	1/2" Nozzle	13.50

Adjustable Nozzle



Washdown Fittings 1/2" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Type	Price £
NAN08	1/2" System	12.00

Tubes &
Hoses



Section 16

3/4" System

Hose Tail Coupling



Washdown Fittings 3/4" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile NV:
Non Valve V: Valve

Part No.	Hose I/D	Price £
NCH12/12	3/4" NV	11.00
NCH12/12V	3/4" V	28.44

Female Coupling



Washdown Fittings 3/4" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile NV:
Non Valve V: Valve

Part No.	Thread BSPP	Price £
NCF12/12	3/4" NV	7.25
NCF12/12V	3/4" V	26.93

Female Plug



Washdown Fittings 3/4" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile BSPP
Thread

Part No.	Thread	Price £
NPF08/12	1/2"	4.03
NPF12/12	3/4"	4.97

Male Plug



Washdown Fittings 3/4" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile BSPP
Thread

Part No.	Thread	Price £
NPM08/12	1/2"	4.03
NPM12/12	3/4"	4.32

Hose Tail Plug



Washdown Fittings 3/4" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Hose I/D	Price £
NPH08/12	1/2"	3.46
NPH12/12	3/4"	3.31

Double Hose Tail Plug



Washdown Fittings 3/4" System Temperature
Range: 80°C (max) Working Pressure: 25bar (max)
Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Hose I/D	Price £
NPH16/12/12	1" & 3/4"	7.20

Adjustable Nozzle



Washdown Fittings 3/4" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile

Part No.	Type	Price £
NAN12	3/4" System	10.99

Spray Nozzle



Washdown Fittings 3/4" System Temperature Range: 80°C (max) Working Pressure: 25bar (max) Material: Nickel Plated Brass - Seal: Nitrile 3/4" BSPP Female Thread

Part No.	Type	Price £
NSF12/12	3/4" Nozzle	18.79

Water Gun



Washdown Fittings - Trigger Guard As Standard - Maximum Pressure: 365psi - Maximum Temperature: 80°C - Flow Rate: 25 lit/min @72psi

Part No.	Inlet BSPP	Price £
WG02	1/2"	43.31

Heavy Duty Water Gun



Washdown Fittings - Maximum Pressure: 365psi - Maximum Temperature: 80° C - Flow Rate: 25 lit/min @ 72psi

Part No.	Inlet BSPP	Price £
WG03	1/2"	30.50

Trigger And Lance Kit



Washdown Fittings - Heavy Duty Kit With Stainless Steel Mechanism - Trigger, 900mm Lance Nozzle Holder Kit-3/8FX 1/4F - Maximum Pressure: 250bar - Maximum Temperature: 150°C - Flow Rate: 40 lit/min @72psi

Part No.	Inlet BSPP	Price £
TLK01	Fixed Inlet	65.79

Spray Nozzle - Brass



Washdown Fittings - BSPP Male Thread

Part No.	Thread	Price £
SN02B	1/8"	5.29
SN04B	1/4"	2.86

High Pressure Spray Nozzle



Washdown Fittings - Spray Nozzle - Stainless Steel - Suitable For Single And Double Lances - BSPP Male Thread

Part No.	Size	Angle	LPM @ 100bar	Price £
SN04/0SS	1/4"	0°	13.6	8.60
SN04/15SS	1/4"	15°	13.6	8.60
SN04/25SS	1/4"	25°	13.6	8.60



For

Valves

see Section 20





Karcher High Pressure Cleaners



KARCHER® K2.120 High Pressure Cleaner



Small, lightweight all-rounder for occasional use for light soiling. For example, garden furniture, bicycles, cars and small areas around the house. Ideal for use as a second machine - Standard accessories: Trigger gun, High-pressure hose, 4 m, One-way spray lance, Dirt Blaster, Adapter garden hose A3/4".

Part No.	Pressure (bar/MPa)	Water flow rate (l/h)	Dimensions (L x W x H) (mm)	Price £
1.673-108	max. 100/max. 10	max. 342	280x176x443	74.99

KARCHER® T250 High Pressure Cleaner



High-performance cleaner for regular use on medium to high soiling levels. The compact design ensures maximum mobility - Standard accessories: High-pressure hose, 6 m, T-Racer T 250 Surface & Patio Cleaner, Vario-power spray lance, Dirt Blaster, Adaptor garden hose A3/4", Trolley.

Part No.	Pressure (bar/MPa)	Water flow rate (l/h)	Dimensions (L x W x H) (mm)	Price £
1.180-137	20-max. 120/2-max. 12	420	330x325x876	249.99

KARCHER® T250 T-Racer Surface And Patio Cleaner



For cleaning flat surfaces (e.g. patios) and vertical surfaces (e.g. garage doors) without splash back. Features two rotating flat jet nozzles for better cleaning results.

Part No.	Description	Price £
3.641-361	Surface And Patio Cleaner	77.40

KARCHER® Extended Easy Press Trigger Gun



Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector.

Part No.	Specification	Price £
4.775-529	Karcher Branded	70.52
4.775-323	K Part non-branded version	34.41

KARCHER® Spray Lance



550mm Stainless Steel Lance, non-rotatable. With manual coupling.

Part No.	Specification	Price £
4.760-665	Karcher Branded	46.84
4.760-584	K Part non-branded version	33.35

Karcher Vacuum Cleaners

KARCHER® T 10/1 Professional Dry Vacuum Cleaner



The new T10/1 Professional is a powerful commercial vacuum cleaner with an excellent container capacity. Ideal for daily maintenance use in vehicles and workshops, this manoeuvrable and compact unit comes complete with a detachable mains cable and cable storage around machine head - Standard Accessories: Suction hose - 2.5 m, Filter bag - Fleece, Washable nylon filter (main filter), Switchable floor nozzle - 260 mm.

Part No.	Air Flow Rate (l/s)	Container Capacity (l)	Max. Intake performance (W)	Dimensions (L x W x H) (mm)	Price £
9.622-182	61	10	1250	355x310x410	134.00

KARCHER® NT 27/1 Wet & Dry Vacuum Cleaner



The NT 27/1 is a powerful wet/dry vacuum cleaner for professional users. It is exceptionally compact and comes standard with a number of useful accessories - Standard accessories: Suction hose - 2.5 m, Metal suction tube - Filter bag - Paper, Wet and dry floor tool - 300 mm, Cartridge filter, Safety class - II.

Part No.	Air Flow Rate (l/s)	Container Capacity (l)	Dimensions (L x W x H) (mm)	Price £
1.428-104	67	27	420x420x525	231.00

FEMALE CLICK X HOSE COMPRESSION - PVC



FEMALE CLICK X HOSE COMPRESSION - PVC

Part No.	Size	Price £
500000	FOR HOSE 1/2" & 5/8" (12-15MM)	0.88
500001	FOR HOSE 3/4" (19MM)	0.93

FEMALE CLICK X HOSE COMPRESSION WITH AUTOMATIC VALVE - PVC



FEMALE CLICK X HOSE COMPRESSION WITH AUTOMATIC VALVE - PVC

Part No.	Size	Price £
500002	FOR HOSE 1/2" & 5/8" (12-15MM)	0.93
500003	FOR HOSE 3/4" (19MM)	1.36

DOUBLE HOSE COMPRESSION - PVC



DOUBLE HOSE COMPRESSION - PVC

Part No.	Size	Price £
500004	FOR HOSE 1/2" & 5/8" (12-15MM)	0.53
500005	FOR HOSE 3/4" (19MM)	0.60

FEMALE THREAD X FEMALE CLICK WITH AUTOMATIC VALVE - PVC



FEMALE THREAD X FEMALE CLICK WITH AUTOMATIC VALVE - PVC

Part No.	Size	Price £
500017	3/4"	1.27

MALE THREAD X FEMALE CLICK - PVC



MALE THREAD X FEMALE CLICK - PVC

Part No.	Size	Price £
500018	3/4"	1.13

MALE CLICK X FEMALE THREAD - PVC



MALE CLICK X FEMALE THREAD - PVC

Part No.	Size	Price £
500006	1/2"	0.38
500007	3/4"	0.38
500008	1"	0.38

Brass Fittings are in Section 8



MALE CLICK X MALE THREAD - PVC



MALE CLICK X MALE THREAD - PVC

Part No.	Size	Price £
500014	1/2"	1.03
500015	3/4"	0.37
500016	1"	1.03

MALE CLICK X DOUBLE SIZE FEMALE THREAD - PVC



MALE CLICK X DOUBLE SIZE FEMALE THREAD - PVC

Part No.	Size	Price £
500009	1/2" X 3/4"	0.99
500019	3/4" X 1"	0.99

MALE CLICK - PVC



MALE CLICK - PVC

Part No.	Size	Price £
500012	DUO (STRAIGHT)	0.43
500013	TRIO (3-WAY)	0.67

IN-LINE VALVES - PVC



IN-LINE VALVES - PVC

Part No.	Size	Price £
500020	MALE CLICK CONNECTIONS	1.51
500022	MALE CLICK X 3/4" FEMALE THREAD	1.51
500023	MALE CLICK X 3/4" MALE THREAD	1.51

3 WAY VALVES - PVC



3 WAY VALVES - PVC

Part No.	Size	Price £
500024	INLET FEMALE 3/4" - 2 X MALE OUTLET 3/4"	1.78
500037	INLET 3/4" FEMALE - 2 X MALE CLICK CONNECTION	1.85

FEMALE CLICK X HOSE COMPRESSION - BRASS



FEMALE CLICK X HOSE COMPRESSION - BRASS

Part No.	Size	Price £
500100	FOR 12/15 MM HOSE	4.78
500101	FOR 16/19 MM HOSE	5.39

FEMALE CLICK X HOSE COMPRESSION WITH WATER STOP - BRASS



FEMALE CLICK X HOSE COMPRESSION WITH WATER STOP - BRASS

Part No.	Size	Price £
500103	FOR 12/15 MM HOSE	5.39
500104	FOR 16/19 MM HOSE	5.60

MALE THREAD X FEMALE CLICK - BRASS



MALE THREAD X FEMALE CLICK - BRASS

Part No.	Size	Price £
500105	3/4"	5.73

For
Malleable Iron
see **Section 11**



MALE THREAD X FEMALE CLICK - BRASS



MALE THREAD X FEMALE CLICK - BRASS

Part No.	Size	Price £
500105	3/4"	5.73

FEMALE THREAD X FEMALE CLICK - BRASS



FEMALE THREAD X FEMALE CLICK - BRASS

Part No.	Size	Price £
500098	3/4"	5.73

DOUBLE HOSE COMPRESSION - BRASS



DOUBLE HOSE COMPRESSION - BRASS

Part No.	Size	Price £
500106	12/15 MM HOSE	4.03
500107	16/19 MM HOSE	4.98

FEMALE THREAD X MALE CLICK - BRASS



FEMALE THREAD X MALE CLICK - BRASS

Part No.	Size	Price £
500108	1/2"	1.84
500109	3/4"	1.84
500110	1"	2.93

MALE THREAD X MALE CLICK - BRASS



MALE THREAD X MALE CLICK - BRASS

Part No.	Size	Price £
500111	1/2"	1.64
500112	3/4"	1.78

DOUBLE MALE CLICK - BRASS



DOUBLE MALE CLICK - BRASS

Part No.	Size	Price £
500114	N/A	2.12

SWIVEL UNION - BRASS



SWIVEL UNION - BRASS

Part No.	Size	Price £
500099	3/4" Female Thread With Male 90° Click Outlet	9.07

DOUBLE OUTLET VALVE FEMALE - BRASS



DOUBLE OUTLET VALVE FEMALE - BRASS

Part No.	Size	Price £
500116	3/4" Female Thread With 2 Manual Valve Male Click Outlets	15.42



For a wide selection of
Pressure Gauges
see **Section 23**



GARDEN NYMPH AUTO HOSE REEL



Garden nymph auto hose reel - Practical and economical wall mounted auto hose reel. Containing 20 metres of high quality green braided garden hose, that can be deployed in measured amounts and automatically recoiled neatly. Wall bracket allows 180° movement and built in handle for easy removal. Supplied complete with connection hose, nozzle and fittings - working pressure : 6 bar - burst pressure : 18 bar - 20 mtrs of 1/2" hose included.

Part No.	Hose Length	Price £
500080	20 Metres	90.58

DOUBLE DUTY HOSE REEL



DOUBLE DUTY HOSE REEL - WITH WALL MOUNTING SET - ADJUSTABLE NOZZLE & CONNECTORS - 20 MTRS OF 1/2" HOSE INCLUDED.

Part No.	Hose Length	Price £
550061	20 Metres	61.38

MEGA NOZZLE



Mega Nozzle - Soft PVC covered brass adjustable nozzle. Heavy duty. Durable PVC handles - 3/4" female thread & male click - 1/2" & 3/4" heavy duty hosetail

Part No.	Description	Price £
451703	METAL WITH FLOW CONTROL	11.04

BRASS NOZZLE



BRASS NOZZLE - Female Thread, Adjustable Flow/Spray.

Part No.	Size	Price £
423830	3/4" X 75 MM LONG	3.34
423831	3/4" X 90 MM LONG	3.48

RP SIX BLUE SPRAY GUN



RP SIX BLUE SPRAY GUN - RUBBER HANDLE - ROTATING PLASTIC NOZZLE WITH 6 SPRAY SETTINGS

Part No.	Size	Price £
1301865	3/4" FEMALE THREAD	15.42

Hydraulic Adaptors are in Section 5



Redashe® GNSS Stainless Steel Water Gun (White)



Redashe trigger operated water guns give fingertip control of water usage in a variety of wash down applications - For use with Redashe hose reels - Features: Easy to use trigger operation - Adjustable spray/jet pattern - Water temperatures up to 95° Celsius - Flow rates up to 60 ltrs a minute - Automatic water shut-off on release of trigger - Water pressures up to 25bar / 367psi - All supplied with safety trigger guard (excludes the XGM)

Part No.	Description	Temp	Pressure psi/bar	Flow Rate	Price £
XGNSS	1/2" BSP Female Inlet	95°C	367 psi / 25 bar	25 ltr/min	182.00

Redashe® GNSS Stainless Steel Water Gun (Red)



Redashe trigger operated water guns give fingertip control of water usage in a variety of wash down applications - For use with Redashe hose reels - Features: Easy to use trigger operation - Adjustable spray/jet pattern - Water temperatures up to 95° Celsius - Flow rates up to 60 ltrs a minute - Automatic water shut-off on release of trigger - Water pressures up to 25bar / 367psi - All supplied with safety trigger guard (excludes the XGM)

Part No.	Description	Temp	Pressure psi/bar	Flow Rate	Price £
XGNSSR	1/2" BSP Female Inlet	95°C	367 psi / 25 bar	25 ltr/min	182.00

